




ADU ADDITION FOR

1651 PARKSIDE AVE. SAN JOSE, CA 95125

DRAWING INDEX:
ARCHITECTURAL

- A. 101 PROPOSED ADU 1st & 2nd FLOOR PLANS
- A. 201 PROPOSED SOUTH & WEST ELEVATIONS
- A. 202 PROPOSED NORTH & EAST ELEVATIONS
- A. 203 CROSS SECTIONS
- A. 301 PROPOSED DOOR & WINDOW SCHEDULE
- A. 401 PROPOSED BUILDING PAPER
- A. 402 HOUSE WRAP DETAILS AROUND WALL TO ROOF TRANSITION (1)
- A. 403 HOUSE WRAP DETAILS AROUND WALL TO ROOF TRANSITION (2)
- A. 501 PROPOSED KITCHEN & BATH INTERIOR ELEVATIONS
- A. 601 3D RENDERS



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office:
3313Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

Date:
APRIL 23, 2019
Scale:

DRAWING TITLE:
COVER SHEET


Sheet :

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD.
PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION
WITH OWNER, PIXELARCH LTD.

Page No. :

A. 000


No.	Revision/Issue	Date
1	ISSUED FOR PLANNING APPROVAL	



PROPOSED ADU 1ST FLOOR PLAN


Scale: 1/4" = 1' - 00"

EMERGENCY ESCAPE / RESCUE OPENING (R310)



NOTE: SIZES ARE TAKEN FROM DATA SUPPLIED BY WINDOW MANUFACTURES. HOWEVER, THESE ARE GENERAL DIMENSIONS AND MUST BE VERIFIED WITH ACTUAL WINDOWS INSTALLED TO MEET MIN. EGRESS REQUIREMENTS.

- SYMBOLS**
- BATHROOM FAN (MAY INCLUDE LIGHT UNIT).
 - SMOKE DETECTOR - HARD WIRED TO ELECTRICAL SYSTEM W/BATTERY BACKUP PROVIDED IN ACCORDANCE WITH THE 2016 CALIFORNIA BUILDING CODE, SECTION R314.
 - COMBINATION SMOKE & CARBON MONOXIDE DETECTOR, HARD WIRED TO ELECTRICAL SYSTEM W/BATTERY BACKUP PROVIDED IN ACCORDANCE WITH THE 2016 CALIFORNIA BUILDING CODE, SECTION R315.



PROPOSED ADU LOFT FLOOR PLAN

Scale: 1/4" = 1' - 00"

SECTION 1026 OF THE 2016 INTERNATIONAL BUILDING CODE /SECTION 310 OF THE 2016 INTERNATIONAL RESIDENTIAL CODE

BASEMENTS IN A DWELLING UNIT AND EVERY SLEEPING ROOM BELOW THE FOURTH STORY (INCLUDES ROOMS WHICH COULD BE USED FOR SLEEPING SUCH AS DENS, SEWING ROOMS, STUDY, ETC.) MUST HAVE A LEAST ONE OPERABLE WINDOW OR DOOR APPROVED FOR EMERGENCY ESCAPE OR RESCUE WHICH SHALL OPEN DIRECTLY INTO A PUBLIC STREET, PUBLIC ALLEY, YARD, OR EXIT COURT. THE UNITS MUST BE OPERABLE FROM THE INSIDE TO PROVIDE A FULL CLEAR OPENING WITHOUT THE USE OF SEPARATE TOOLS.

FOR FULL EGRESS, ESCAPE OR RESCUE WINDOWS ARE REQUIRED TO HAVE A MINIMUM NET CLEAR OPEN-ABLE AREA OF 5.7 SQ. FT. (820.8 SQ IN). EXCEPTION: MAY BE REDUCED TO 5.0 SF (720 SQ IN) IF 44" OR LESS FROM EXTERIOR GROUND LEVEL TO SILL. THE MINIMUM NET CLEAR OPEN-ABLE HEIGHT DIMENSION MUST BE 24 INCHES. THE MINIMUM NET CLEAR OPEN-ABLE WIDTH DIMENSION MUST BE 20 INCHES. THEY MUST ALSO HAVE A FINISHED SILL HEIGHT (CLEAR OPENING) OF NOT MORE THAN 44 INCHES ABOVE THE FLOOR. IN ORDER TO MEET THE REQUIRED NET-CLEAR OPEN AREA SQUARE-FOOT OPENING, EITHER THE WIDTH OR HEIGHT OR BOTH MUST EXCEED THE MINIMUM DIMENSIONS THEREOF. WHEN REPLACING EXISTING NONCONFORMING WINDOWS REQUIRED FOR EMERGENCY ESCAPE AND RESCUE THE REPLACEMENT WINDOWS MUST MEET THE FOLLOWING:

EMERGENCY ESCAPE AND RESCUE REPLACEMENT WINDOW OPENINGS SHALL HAVE A MINIMUM NET CLEAR OPENING OF 4 SQ. FT.; MINIMUM NET CLEAR OPENING HEIGHT OF 22 INCHES; MINIMUM NET CLEAR OPENING WIDTH OF 20 INCHES. MINIMUM SILL HEIGHT OF NOT MORE THAN 48 INCHES ABOVE THE FLOOR OR THE INSTALLATION OF ONE OR MORE PERMANENTLY AFFIXED STEPS EXTENDING THE FULL WIDTH OF THE WINDOW OPENING, CONSTRUCTED TO THE CURRENT ADOPTED IRC RISE AND RUN DIMENSIONAL REQUIREMENTS, SO THAT THE TOP STEP IS NO GREATER THAN 44 INCHES TO THE TOP OF THE SILL WHERE THE EXISTING ROUGH OPENING DOES NOT ALLOW FOR REPLACEMENT WINDOW DIMENSIONAL REQUIREMENTS THE ROUGH OPENING SHALL BE ENLARGED AND THE REPLACEMENT WINDOW SHALL MEET THE FULL EMERGENCY ESCAPE AND RESCUE OPENINGS PER IRC SECTION R310.1 THROUGH R310.5 OR IBC SECTION 1026 AS APPLICABLE FOR SCOPE OF PROJECT.

ADDITIONAL GLAZING REQUIREMENTS:

FOR MINIMUM LIGHT, ALL SLEEPING ROOMS AND OTHER HABITABLE ROOMS REQUIRE GLAZING EQUAL TO AT LEAST 8% OF THE FLOOR AREA OF THE ROOM; MINIMUM VENTILATION OF 4% OF THE FLOOR AREA. SEE THE INTERNATIONAL BUILDING OR RESIDENTIAL CODES AS APPLICABLE FOR EXCEPTIONS AND A COMPLETE LIST OF LIGHT AND VENTILATION REQUIREMENTS.

SAFETY GLAZING IS REQUIRED IN DOORS, STORM DOORS, RAILINGS, WITHIN 24 INCHES OF A DOOR, OR WHEN PANES ARE OVER 9 SQUARE FEET AND WITHIN 18 INCHES OF THE FLOOR. SEE THE INTERNATIONAL BUILDING OR RESIDENTIAL CODES FOR EXCEPTIONS AND A COMPLETE LIST OF SAFETY GLAZING REQUIREMENTS.

FLOOR PLAN SHEET NOTES

- GENERAL CONTRACTOR TO BE RESPONSIBLE FOR ADEQUATELY FRAMING, BRACING, AND STRUCTURING ALL WALLS AND OTHER GYPSUM BOARD CONSTRUCTION IN ACCORDANCE WITH APPLICABLE TYPICAL DETAILS CONTAINED IN THESE DRAWINGS. WHETHER OR NOT SPECIFICALLY REFERENCED IN THE PLANS, ALL PARTITIONS SHALL BE BRACED IN ACCORDANCE WITH SEISMIC CODE REQUIREMENTS.
- COORDINATE AND INSTALL BACKING AS REQUIRED FOR ALL NEW MILLWORK, MARKERBOARDS, EQUIPMENT, FURNITURE, PROJECTION SCREENS, ETC.
- ALL PARTITIONS ARE DIMENSIONED FROM FACE OF FINISH TO FACE OF FINISH, U.O.N.
- PARTITIONS SHOWN TO ALIGN WITH FACE OF EXISTING CONSTRUCTION OR NEW PARTITIONS SHOULD ALIGN FINISHED FACE TO FINISHED FACE.
- DIMENSIONS INDICATED TO BE "CLEAR" OR TO HOLD SHALL BE MAINTAINED AND DISCREPANCIES OR VARIATIONS ON THESE DIMENSIONS SHALL BE REVIEWED WITH ARCHITECT BEFORE BEGINNING CONSTRUCTION.
- PREPARE ALL GYP. BD. WALL SURFACES TO RECEIVE PARTITIONS, AND WALL FINISHES.
- FLOOR TOLERANCE: FINISHED FLOOR TO BE LEVELED TO A TOLERANCE OF 1/4" SLOPE IN 10 FEET. GENERAL CONTRACTOR TO IMMEDIATELY VERIFY SLOPE AND REPORT ANY DEVIATIONS FROM ABOVE STATED TOLERANCE TO PIXELARCH LTD.
- PRIOR TO COMMENCING WORK ALIGNMENT OF DOOR HEADS AND OTHER CRITICAL HORIZONTAL ELEMENTS SHALL BE MAINTAINED AT A CONSTANT LEVEL AND SHALL NOT FOLLOW VARIATIONS IN THE FLOOR PLATES.
- THERMOSTATS TO BE LOCATED ABOVE LIGHT SWITCHES, TYP.
- MULTIPLE LIGHT SWITCHES TO BE GANGED WITHIN A SINGLE COVER-PLATE TO MAXIMUM EXTENT POSSIBLE. WHERE MULTIPLE SWITCHES CANNOT BE GANGED WITHIN A SINGLE COVER-PLATE, SWITCHES ARE TO BE ADJACENT TO EACH OTHER OR AS CLOSE AS POSSIBLE.
- GO TO PROVIDE ALL APPLIANCES AND FIXTURES, U.O.N.
- THE CONTRACTOR SHALL "STRIKE OUT" LOCATION OF ALL WALLS, DOORS, MULLIONS, SOFFITS, RAISED FLOOR GRIDS, HOUSEKEEPING AND UTILITY EQUIPMENT PADS, AND OTHER MAJOR ELEMENTS, OR AS DIRECTED BY ARCHITECT AT THE BEGINNING OF THE PROJECT BEFORE PROCEEDING WITH CONSTRUCTION. IF DISCREPANCIES EXIST BETWEEN FIELD CONDITIONS AND THE DRAWINGS NOTIFY ARCHITECT.
- ALL FURRED WALLS SHALL EXTEND VERTICALLY THRU THE CEILING WHERE INDICATED ON THE DRAWINGS OR TO THE STRUCTURE ABOVE WHERE NO CEILING OCCURS. U.O.N.
- HINGE SIDE OF DOORS TO BE LOCATED PER DETAILS FROM THE FACE OF ADJACENT PERPENDICULAR PARTITIONS. U.O.N.
- REFER TO ENLARGED PLANS FOR DIMENSIONS AND INFORMATION WHEN DESIGNATED.
- THE GENERAL CONTRACTOR SHALL COORDINATE AND PROVIDE APPROPRIATE STRUCTURAL BACKING AND REINFORCING IN PARTITIONS BEHIND ALL WALL-MOUNTED, WALL ANCHORED OR SUPPORTED ITEMS. ALL CONCEALED WOOD USED FOR SUCH SUPPORT SHALL BE FIRE RETARDANT TREATED.
- IN THE EVENT OF CONFLICT BETWEEN DATA SHOWN ON DRAWINGS AND DATA SHOWN ON THE SPECIFICATIONS, THE DRAWINGS SHALL TAKE PRECEDENCE. DETAIL DRAWINGS TAKE PRECEDENCE OVER DRAWING OF SMALLER SCALE. SHOULD THE CONTRACTOR AT ANY TIME DISCOVER AN ERROR IN A DRAWING OR SPECIFICATION OR A DISCREPANCY OR VARIATION BETWEEN DIMENSIONS ON DRAWINGS AND MEASUREMENTS AT THE SITE OR LACK OF DIMENSIONS OR OTHER INFORMATION, THE GENERAL CONTRACTOR SHALL NOT PROCEED WITH THE WORK AFFECTED UNTIL CLARIFICATION HAS BEEN MADE.
- PROVIDE BACKING AS REQUIRED PER FURNITURE REQUIREMENTS.
- THE FOLLOWING SHALL BE PROVIDED BY THE GENERAL CONTRACTOR AS DESIGN-BUILD SYSTEMS (IF SUCH SYSTEMS ARE REQUIRED BY THE CITY):
 - AUTOMATIC FIRE SPRINKLER SYSTEM.
CONTRACTOR SHALL FULLY COORDINATE THE DESIGN/ENGINEERING PROCESS OF THE ABOVE REFERENCED SYSTEMS AND THE COMPLETE AND PROPERLY FUNCTIONING INSTALLATION THEREOF.
 - TELECOMMUNICATIONS
 - SECURITY
- THE GENERAL CONTRACTOR SHALL PROVIDE ELECTRICAL RACEWAY AND POWER TO ALL POINTS DESIGNATED BY THE VENDOR'S FOR EACH OF THE OWNER'S FURNISHED SYSTEMS.
- ALL PARTITIONS, DOORS, GLAZED OPENINGS, SOFFITS, ETAL., SHALL BE STRUCTURALLY BRACED IN ACCORDANCE WITH SEISMIC CODE REQUIREMENTS.
- COORDINATE LOCATION AND PROVIDE BLOCKING, BACKINGS AND/OR REINFORCEMENT IN PARTITIONS FOR ALL CABINETS, COUNTERTOPS AND ANY WALL-MOUNTED ITEMS. REFER TO THE PLANS, ELEVATIONS AND DETAILS FOR LOCATION OF ITEMS WHICH MAY REQUIRE SUPPORT.
- THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING THE DIMENSIONS AND ELEVATIONS AT THE SITE. THE CONTRACTOR AND SUB-CONTRACTORS SHALL COORDINATE THE LAYOUT AND EXACT LOCATIONS OF ALL PARTITIONS, DOORS, ELECTRICAL/TELEPHONE OUTLETS, LIGHTSWITCHES AND THERMOSTATS WITH THE ARCHITECT IN THE FIELD PRIOR TO PROCEEDING.
- WHEREVER DIAGONAL BRACING IS INDICATED OR OTHERWISE REQUIRED, INSTALL BRACING UNEXPOSED TO VIEW, PARTICULARLY AT SUSPENDED OR DRYWALL CEILING AREAS. IF EXPOSED TO VIEW CONDITIONS EXIST IN THE DESIGN, DO NOT BRACE INTO THE AREA WHERE NO CEILING IS TO BE INSTALLED, OR INTO THE "MORE OPEN" AND VISIBLE SIDE OF BULKHEAD/SOFFIT WHERE BOTH SIDES SHALL BE WITHOUT A CEILING.
- WHERE NEW PARTITIONS MEET EXISTING MULLIONS OR COLUMNS INSTALL THE NEW PARTITION PERPENDICULAR TO THE EXISTING MULLION OR COLUMN AND ALIGN THE CENTERLINE OF THE NEW PARTITION WITH THE MULLION OR COLUMN U.O.N.
- WHERE A GYPSUM BOARD PARTITION MEETS FLUSH WITH THE FACE OF AN EXISTING PARTITION, REMOVE THE EXISTING METAL CORNER BEAD BEFORE INSTALLING THE NEW PARTITION.
- ALIGN NEW PARTITION SURFACES WITH THE EXISTING ADJACENT OR ADJOINING SURFACES WHERE INDICATED. TAPE AND SAND THE JOINTS TO SMOOTH WITHOUT ANY VISIBLE JOINTS. PATCH AND REPAIR SURFACES TO MATCH ADJACENT OR ADJOINING SURFACES.
- PATCH EXISTING DAMAGED PARTITIONS THROUGHOUT ENTIRE PROJECT AREA TO MATCH ADJACENT SURFACES.
- CUT AND FIT COMPONENTS AS REQUIRED TO ALTER EXISTING WORK FOR INSTALLATION OF NEW WORK. PATCH DAMAGED AREAS TO MATCH ADJACENT SURFACES.
- AT OPENINGS IN GYPSUM BOARD WALLS FOR DUCT WORK, RETURN AIR, WRAP HEAD, JAMBS AND SILL OF OPENING WITH GYPSUM BOARD. U.O.N.
- VERTICAL DIMENSIONS ARE FROM TOP OF FLOOR SLAB, EXCEPT WHERE OTHERWISE NOTED TO BE ABOVE FINISH FLOOR.
- DIMENSION ARE NOT ADJUSTABLE WITHOUT APPROVAL OF THE ARCHITECT UNLESS NOTED +/- OR VIF.
- THE GENERAL CONTRACTOR SHALL VERIFY THAT NO CONFLICT EXIST IN THE LOCATION OF ANY MECHANICAL, HVAC, TELEPHONE, ELECTRICAL, PLUMBING AND SPRINKLER EQUIPMENT (TO INCLUDE ALL PIPING, DUCTWORK, CONDUIT, CABLES, ETC.) AND THAT ALL REQUIRED CLEARANCES FOR INSTALLATION AND MAINTENANCE OF ABOVE EQUIPMENT ARE PROVIDED. ELEMENTS TO BE EXPOSED TO VIEW SHALL BE REVIEWED WITH THE ARCHITECT AND COORDINATED BY AND BETWEEN THE GENERAL CONTRACTOR AND PERTINENT SUB-CONTRACTORS PRIOR TO CONSTRUCTION OR FABRICATION PROCEEDING.



PixelArch Ltd.

US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office:
3355 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODEL AND ADU ADDITION FOR
CUONG NGUYEN
1651 PARKSIDE AVE, SAN JOSE, CA 95125

Date:
APRIL 23, 2019
Scale:
1/4"=1'-00"

DRAWING TITLE:
PROPOSED ADU FLOOR PLANS

Sheet :
1 OF 10

Page No. :


A.101

No.	Revision/Issue	Date
1	ISSUED FOR PLANNING APPROVAL	



PROPOSED ADU SOUTH (FRONT) ELEVATION

Scale: 1/4" = 1' - 00"



PROPOSED ADU WEST ELEVATION

Scale: 1/4" = 1' - 00"

FINISH NOTES:

RENDERINGS ARE NOT TO SCALE; ALL RENDERINGS ARE FOR ARTISTIC DEPICTION ONLY. PLAN UPDATES MAY NOT BE REFLECTED IN RENDERINGS. RENDERINGS SHALL NOT BE USED FOR CONSTRUCTION.

BASE BOARDS SHALL BE 6" IN ALL ROOMS. UNO.

FINAL FINISHES SHALL BE CONFIRMED WITH THE HOME OWNER PRIOR TO APPLICATION.



EXTERIOR FINISH NOTES:

EXTERIOR FINISH TO BE FIBER CEMENT SIDING OVER 5/8 CDX PLYWOOD. WINDOW & DOOR TRIM CEDAR. MATERIAL AND COLOR BY OWNER.


ROOFING TO BE EXPOSED FASTENER METAL ROOFING OVER 30# FELT, 5/8 CDX PLYWOOD. DECKING TO BE TREX OR WOOD. FINAL MATERIAL AND COLOR BY OWNER.

CHIMNEYS ARE DECORATIVE AND PROVIDE FOR VENTING OF GAS FIREPLACES ONLY. DOWNSPOUTS TO BE COLLECTED AND ROOF RUN OFF TO BE DIRECTED AWAY FROM STRUCTURE PER THE SITE PLAN.


FINISH GRADE SHALL SLOPE AWAY FROM STRUCTURE MIN. 1/2" PER FOOT OF RUN FOR 4' MIN. BASALT RETAINING WALLS TO MATCH EXISTING RETAINING WALL.



HARDIEPLANK HZ10 5/16 IN. X 8.25 IN. X 144 IN. FIBER CEMENT SELECT CEDARMILL LAP SIDING



5V CRIMP EXPOSED FASTENER METAL ROOFING



TYPICAL WALL ISOMETRIC
RESIDENTIAL WOOD FRAME STRUCTURE w/ VINYL SIDING



PixelArch Ltd.

US Office:
1442N. Dale Ave. Anaheim, CA 92801

Canada Office:
3370 Pateau Blvd. Coquitlam BC V3E 3B8

+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODEL AND ADU ADDITION FOR
CUONG NGUYEN
1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:
APRIL 23, 2019

Scale:
1/4"=1'-00"

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.


DRAWING TITLE:
PROPOSED SOUTH AND WEST ELEVATIONS

Sheet :
2 OF 10

Page No. :


No.	Revision/Issue	Date
1	ISSUED FOR PLANNING APPROVAL	
2		
3		
4		

A. 201



PROPOSED ADU NORTH ELEVATION

Scale: 1/4" = 1' - 00"



PROPOSED ADU EAST ELEVATION

Scale: 1/4" = 1' - 00"

NOTES

- ATTICS; ACCESS PER CRC R807, DRAFTSTOPS PER CRC R302.10 & R502.12 AND VENTILATION PER R806 & R408.1.
- WHERE EMERGENCY ESCAPE AND RESCUE OPENINGS ARE PROVIDED, THEY SHALL HAVE THE BOTTOM OF THE CLEAR OPENING NOT GREATER THAN 44" MEASURED FROM THE FLOOR.
- PER CRC 310.1.
- GLAZING IN ENCLOSURES FOR WALLS FACING HOT TUBS, WHIRLPOOLS, SAUNAS, STEAM ROOMS, BATHTUBS AND SHOWERS WHERE THE BOTTOM EXPOSED EDGE IS LESS THAN 60" MEASURED VERTICALLY ABOVE A STANDING OR WALKING SURFACE. PER CRC R308, R303.1.7 R301.2.1.2.
- FACTORY-BUILT FIREPLACES AND CHIMNEYS PER CRC R1004, R1005, R1006, A.Q.M.D. RULE 445, AND CAL-GREEN SECTION 4.503.1.
- COMBUSTION AIR TO FORCED AIR UNIT PER CMC CHAPTER 7.
- COMBUSTION AIR TO WATER HEATER PER CPC SECTION 507.0.
- ENVIRONMENTAL AIR DUCTS PER CMC SECTION 504.
- MECHANICAL EQUIPMENT LOCATION AND PROTECTION AGAINST DAMAGE PER CMC 307.
- PER THE BUILD IT GREEN PROGRAM'S "GREENPOINT RATING CHECKLIST" SECTION P(D)2, MOISTURE MATERIALS SHALL BE USED IN WET AREAS (i.e. KITCHEN, BATHROOM, UTILITY ROOMS, ETC.) EXTERIOR DOOR LANDING SHALL BE A MAX. OF 7-3/4" BELOW DOOR THRESHOLD PER CRC R311.3.2.
- GRADE NEEDS TO FALL 6" WITHIN THE FIRST 10'
- CONCRETE SLAB THICKNESS FOR PORCH AND PATIO SLAB SHALL BE 3 1/2" MIN. REQUIRED PER R506.1

EXTERIOR ELEVATION NOTES

- NOTES AND SYMBOLS ARE TO APPLY AT ALL AREAS OF SIMILAR GRAPHIC REPRESENTATION. SUCH INDICATIONS MAY BE LIMITED TO PROMOTE CLARITY OR AVOID REDUNDANCY.
- SLOPE FINISH GRADE 2% MINIMUM AWAY FROM BUILDING FOR 5'-0" MINIMUM, DIRECT DRAINAGE AWAY FROM BUILDING WALLS TO ELIMINATE PONDING.
- REFER TO MECHANICAL AND ELECTRICAL DRAWINGS FOR GRILLES, REGISTERS, HORNS, SPEAKERS, PANELS, PULL STATIONS AND OTHER FEATURES NOT OTHERWISE SHOWN
- FLASH AND SEAL ALL PENETRATIONS THROUGH EXTERIOR ROOFS AND WALLS, AND FLOORS WEATHER TIGHT AND WATERPROOF. PACK ALL PENETRATIONS THROUGH THE BUILDING INSULATION ENVELOPE WITH INSULATION.
- FLASH ALL WINDOWS, DOORS, LOUVERS, ACCESS PANELS AND SIMILAR WALL OPENINGS PER DETAILS ON SHEET A401.
- FIREBLOCKING, CBC 717.2.: PROVIDE MATERIALS COMPLYING WITH CBC 717.2.1 AT CONCEALED SPACES, FURRED SPACES, CEILING/FLOOR LEVELS AND 10'-0" INTERVALS ALONG LENGTH OF WALL, SOFFITS, DROP CEILINGS, AND COVE CEILINGS, CONCEALED PLACES BETWEEN STAIR STRINGERS & BETWEEN STUDS IN LINE WITH STAIR RUN, AND ALL LOCATIONS LISTED IN CBC 717.2.2 THROUGH 717.2.7.
- FLOOR/CEILING DRAFTSTOPPING, CBC 717.3: PROVIDE MATERIALS COMPLYING WITH CBC 717.3.1. AT FLOOR/CEILING ASSEMBLIES AS REQUIRED BY CBC 717.3.2 THROUGH 717.3.3. -GROUP R-1, R-2, R-3, R-4
EXCEPTION: DRAFTSTOPPING NOT REQUIRED IN BUILDINGS SPRINKLERED PER CBC 903.3.1.1.
EXCEPTION: DRAFTSTOPPING NOT REQUIRED IN BUILDINGS SPRINKLERED PER CBC 903.3.2.1 WHEN SPRINKLERS ARE INSTALLED IN THE COMBUSTIBLE CONCEALED SPACES
- ATTIC DRAFTSTOPPING, CBC 717.4: PROVIDE MATERIALS COMPLYING WITH CBC 717.3.1. IN ATTICS AND CONCEALED ROOF SPACES AS REQUIRED BY CBC 717.4.2 THROUGH 717.4.3. PROVIDE SELF-CLOSING DOORS WITH AUTOMATIC LATCHES CONSTRUCTED AS REQUIRED FOR DRAFTSTOPPING PARTITIONS.
- REFER TO REFLECTED CEILING PLAN FOR LOCATION OF CLERESTORY WINDOWS, TYPICAL.
- ELEVATIONS SHOWN ARE MEASURED FROM FINISHED FLOOR DATUM FOR THIS BUILDING.
- NEW WORK PROVIDE BLOCKING, BACKING, FRAMING, SHEATHING, UTILITIES OR OTHER CONCEALED WORK, WHETHER SPECIFICALLY SHOWN OR INFERRED. REFER TO STRUCTURAL DRAWINGS FOR CONCEALED WORK NOT SHOWN ON ARCHITECTURAL DRAWINGS.
- REMODEL/ADDITION WORK NEATLY CUT AND REMOVE SURFACES AND FINISHES AS REQUIRED OR TO A NATURAL POINT OF DIVISION TO ENABLE INSTALLATION OF BLOCKING, BACKING, FRAMING, SHEATHING, UTILITIES OR OTHER CONCEALED WORK, WHETHER SPECIFICALLY SHOWN OR INFERRED FOR SUPPORT OR RENOVATION. REFER TO STRUCTURAL DRAWINGS FOR CONCEALED WORK NOT SHOWN ON ARCHITECTURAL DRAWINGS.
- REPAIR AND REPLACE ALL EXISTING SURFACES AND FINISHES TO MATCH EXISTING UNDISTURBED WORK.
- ALL NEW ADDITION WORK FINISHES AND COLORS FOR SIDING, TRIM, WINDOWS, ROOFING, ETC. ARE TO MATCH EXISTING FINISHES AND COLORS.



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3313 Paterson Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODEL AND ADU ADDITION FOR
CUONG NGUYEN
1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:
APRIL 23, 2019

Scale:
1/4"=1'-00"

COPYRIGHT

THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

DRAWING TITLE:

PROPOSED NORTH AND EAST ELEVATIONS


Sheet :

3 OF 10

Page No. :

A. 202

No.	Revision/Issue	Date
1	ISSUED FOR PLANNING APPROVAL	



PROPOSED CROSS SECTION 1

Scale: 1/4" = 1' - 00"

BUILDING CODE REQUIREMENT

ANY ACCESS DOOR TO THE CRAWL SPACE MUST BE AT LEAST 18X24 INCHES (2015 INTERNATIONAL CONFORM TO SPECIFICATIONS RESIDENTIAL CODE (IRC) - SECTION R408.4).

ANY DRAIN LOCATED IN THE CRAWL SPACE MUST BE ALLOWED TO RUN OFF AND TERMINATE OUTDOORS OR NEED TO MEET SPECIFICATIONS TO AN INTERIOR CRAWL SPACE DRAIN OR SUMF PUMP. CRAWL SPACE DRAINS MAY NOT RUN OFF TO GUTTERS OR FOUNDATION PERIMETER DRAINS, AND DRYER VENTS MUST BE TERMINATED OUTDOORS (2015 IRC - SECTIONS R405 AND P2719).

(R408.1), 2009 IRC- OPENINGS FOR UNDER-FLOOR VENTILATION:


THE MINIMUM NET AREA OF VENTILATION OPENINGS SHALL NOT BE LESS THAN 1 SQUARE FOOT (0.0929 M2) FOR EACH 150 SQUARE FEET (14 M2) OF UNDER-FLOOR SPACE AREA.

$600/150 = 4$ SF

$(8" \times 16")$ VENT DIMENSION = .88 SF


$4/.88 = 4.5$

5 VENTS REQUIRED 9 VENTS DESIGNED




7" CLOSED-CELL SPRAY FOAM AGAINST UNDERSIDE OF SHEATHING

1
A.203




9



TYPICAL WALL SECTION


Scale: 3/8" = 1' - 00"

10



PROPOSED CROSS SECTION 2

Scale: 1/4" = 1' - 00"



PROPOSED ROOF PLAN

Scale: 1/4" = 1' - 00"



PixelArch Ltd.

US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office:
3313 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODEL AND ADU ADDITION FOR
CUONG NGUYEN
1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:
APRIL 23, 2019
Scale:
1/4"=1'-00"


DRAWING TITLE:
**PROPOSED CROSS SECTIONS
AND ROOF PLAN**

Sheet :
4 OF 10


Page No. :

A. 203


No.	Revision/Issue	Date
1	ISSUED FOR PLANNING APPROVAL	
2		
3		
4		




11 1ST FLOOR
NTS




12 2ND FLOOR
NTS




1 SLIDING GLASS DOOR HEAD/SILL
NTS




2 WINDOW HEAD/SILL
NTS



3 HARDIE SILL
NTS



4 HARDIE TRIM
NTS




5 HARDIETRIM BOARD
NTS

DOOR SCHEDULE															
NUMBER	LABEL	QTY	FLOOR	SIZE	WIDTH	HEIGHT	R/O	DESCRIPTION	HEADER	THICKNESS	MANUFACTURER	ROOM NAME	SHGC	SWING SIDE	U-FACTOR
D01	2668	1	1	2668 L	30"	80"	32"x82 1/2"	2 DR. BIFOLD-LOUVERED	2X6X35" (2)	1 3/8"	to be chosen by owner	LIVING/CLOSET	0.3	IN	0.35
D02	2668	1	1	2668 L EX	30"	80"	32"x83"	EXT. HINGED-DOOR L05	2X6X35" (2)	1 3/4"	to be chosen by owner	KITCHEN	0.3	IN	0.35
D03	2668	1	1	2668 L IN	30"	80"	32"x82 1/2"	HINGED-DOOR PS02	2X6X35" (2)	1 3/8"	to be chosen by owner	LIVING/BATH	0.3	OUT	0.35
D04	2668	1	1	2668 R IN	30"	80"	32"x82 1/2"	HINGED-DOOR PS02	2X6X35" (2)	1 3/8"	to be chosen by owner	BEDROOM/LIVING	0.3	IN	0.35
D05	3068	1	1	3068 R EX	36"	80"	38"x83"	EXT. HINGED-DOOR L05	2X6X41" (2)	1 3/4"	to be chosen by owner	LIVING	0.3	IN	0.35
D06	3068	1	1	3068 R IN	36"	80"	38"x82 1/2"	HINGED-DOOR PS02	2X6X41" (2)	1 3/8"	to be chosen by owner	BEDROOM/CLOSET	0.3	IN	0.35

WINDOW SCHEDULE															
NUMBER	LABEL	QTY	FLOOR	SIZE	WIDTH	HEIGHT	R/O	EGRESS	DESCRIPTION	HEADER	MANUFACTURER	COMMENTS	SHGC	U-FACTOR	TEMPERED
W01	2010RS	1	1	2014RS	24 "	12 "	25"X13"		RIGHT SLIDING	2X6X28" (2)	to be chosen by owner		0.4	0.35	TEMP. GLAZING
W02	2030DH	1	1	2030DH	24 "	36 "	25"X37"		DOUBLE HUNG	2X6X28" (2)	to be chosen by owner		0.4	0.35	
W03	2638DH	5	1	2638DH	30 "	44 "	31"X45"		DOUBLE HUNG	2X6X34" (2)	to be chosen by owner		0.4	0.35	
W04	2838DH	2	DOWNER WINDOW	2838DH	32 "	44 "	33"X45"		DOUBLE HUNG	2X6X36" (2)	to be chosen by owner		0.4	0.35	
W05	3036CU	1		1	3036CU	36 "	42 "	36 1/2" X 42 1/2"		GARDEN	2X6X39" (2)	to be chosen by owner		0.4	0.35

ENERGY NOTES

- ALL OPENABLE WINDOWS AND SLIDING DOORS SHALL LIMIT AIR LEAKAGE AND BE CERTIFIED AND LABELED TO COMPLY WITH ANSI STANDARD AIS 4.2-1972.
- FIXED WINDOWS SHALL BE SEALED TO LIMIT AIR INFILTRATION.
- ALL EXTERIOR DOORS AND WINDOWS ARE TO BE WEATHERSTRIPPED.
- SITE BUILT DOORS MOUNTED ON THE INSIDE OR THE OUTSIDE OF EXTERIOR WALLS SHALL HAVE A MIN. 1" LAP AT JAMBS.
- OPEN EXTERIOR JOINTS AROUND WINDOW AND DOOR FRAMES BETWEEN WALLS, FOUNDATIONS, ROOFS, PANELS, AND AT PENETRATION OF UTILITIES THRU THE ENVELOPE, SHALL BE SEALED, CAULKED, OR WEATHERSTRIPPED TO LIMIT AIR LEAKAGE.
- PROVIDE A "CERTIFICATE OF COMPLIANCE" SIGNED BY THE OWNER, G.C., ARCHITECT, OR ENGINEER TO THE BLDG. DEPARTMENT STATING THAT THE WORK HAS BEEN PERFORMED AND MATERIALS INSTALLED ACCORDING TO THE PLANS AND SPECIFICATIONS AFFECTING NON-RESIDENTIAL ENERGY.
- INSULATION SHALL BE INSTALLED TO MEET FLAME SPREAD AND SMOKE DENSITY REQUIREMENTS OF 5311 AND TITLE 24.



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office:
3319 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODEL AND ADU ADDITION FOR
CUONG NGUYEN
1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:
APRIL 23, 2019
Scale:
1/4"=1'-00"

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD.
PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION
WITH OWNER, PIXELARCH LTD.















DRAWING TITLE:
PROPOSED DOOR & WINDOW SCHEDULE

Sheet :
5 OF 10

Page No. :

A. 301

No.	Revision/Issue	Date
1	ISSUED FOR PLANNING APPROVAL	

				
WINDOW HEAD @ WD. BOARD & BATTEN SIDING12	WINDOW HEAD @ HORIZONTAL SIDING9	BUILDING PAPER-SECOND COURSE7	WINDOW INSTALLATION4	ROUGH WINDOW OPENING1
				
WINDOW JAMB @ WD. BOARD & BATTEN SIDING13	WINDOW JAMB@HORIZONTAL SIDING10	TRIM-FLASHING-PROTECTION COURSE8	SELF-ADHESIVE MEMBRANE5	SILL FLASHING2
				
WINDOW SILL @ WD. BOARD & BATTEN SIDING14	WINDOW SILL @ HORIZONTALN SIDING11		BUILDING PAPER- FIRST COURSE6	JAMB FLASHING3



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office:
3319Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2595 Info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODEL AND ADU ADDITION FOR
CUONG NGUYEN
1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:
APRIL 23, 2019
Scale:
NTS

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD.
PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION
WITH OWNER, PIXELARCH LTD.


DRAWING TITLE:
**PROPOSED BUILDING PAPER/ HOUSE
WRAP DETAILS AROUND WINDOWS**


Sheet :
6 OF 10

Page No. :

A. 401

No.	Revision/Issue	Date
1	ISSUED FOR PLANNING APPROVAL	








KITCHEN FLOOR PLAN

Scale: 1/2" = 1' - 00"




KITCHEN INTERIOR ELEVATION

Scale: 1/2" = 1' - 00"



KITCHEN PERSPECTIVE VIEW

NTS



BATHROOM FLOOR PLAN

Scale: 1/2" = 1' - 00"

BATHROOM INTERIOR. ELEVATION

Scale: 1/2" = 1' - 00"




BATHROOM INTERIOR. ELEVATION

Scale: 1/2" = 1' - 00"



BATH PERSPECTIVE VIEW

Scale: 1/2" = 1' - 00"



KITCHEN INTERIOR ELEVATION

Scale: 1/2" = 1' - 00"

FIXTURE SCHEDULE									
LABEL	QTY	FLOOR	WIDTH	DEPTH	HEIGHT	DESCRIPTION	CODE	MANUFACTURER	COMMENTS
AC OUTDOOR COMPRESSOR	1	1	31 "	12 3/4 "	29 1/2 "	AC OUTDOOR COMPRESSOR			All appliance, finish fixtures to be determined by owner
BOWL (UNDERMOUNT) SINK [12 7/16W]	1	1	12 7/16 "	14 11/16 "	11 7/16 "	BOWL (UNDERMOUNT) SINK [12 7/16W]			All appliance, finish fixtures to be determined by owner
DUCTLESS AC HEAT	2	1	43 3/16 "	8 11/16 "	12 5/8 "	DUCTLESS AC HEAT			All appliance, finish fixtures to be determined by owner
FAUCET (ARC)	4	1	12 5/16 "	8 5/16 "	12 "	FAUCET (ARC)			All appliance, finish fixtures to be determined by owner
GDE25ESKSS	1	1	32 13/16 "	37 1/2 "	69 7/8 "	GDE25ESKSS	GE		All appliance, finish fixtures to be determined by owner
GDT635H	1	1	23 3/4 "	24 "	30 1/4 "	GDT635H	GE		All appliance, finish fixtures to be determined by owner
GFD48ES	2	1	28 "	34 3/8 "	39 3/8 "	GFD48ES	GE		All appliance, finish fixtures to be determined by owner
K-3325-HCF UNDERTONE, PRESERVE UNDER-MOUNT KITCHEN SINK	1	1	23 "	17 9/16 "	10 3/8 "	K-3325-HCF UNDERTONE, PRESERVE UNDER-MOUNT KITCHEN SINK	KOHLER		All appliance, finish fixtures to be determined by owner
K-3639	1	1	30 "	36 "	26 3/16 "	K-3639 ARCHER TOILET	KOHLER		All appliance, finish fixtures to be determined by owner
K-99270	1	1	13 7/8 "	4 3/4 "	12 7/16 "	K-99270 ARTIFACTS POT FILLER KITCHEN SINK FAUCET	KOHLER		All appliance, finish fixtures to be determined by owner
PW302418	1	1	29 15/16 "	22 1/8 "	18 7/8 "	30" PRO WALL HOOD - 24" DEPTH	SUB-ZERO GROUP, INC		All appliance, finish fixtures to be determined by owner
TANKLESS WATER HEATER	1	1	15 3/4 "	9 "	28 "	TANKLESS WATER HEATER			All appliance, finish fixtures to be determined by owner
TUB-SHOWER 5	1	1	60 "	30 1/2 "	83 1/4 "	TUB-SHOWER 5			All appliance, finish fixtures to be determined by owner
VGIC245-4B RANGE	1	1	23 7/8 "	27 3/4 "	37 1/8 "	VGIC245-4B RANGE	VIKING RANGE CORPORATION		All appliance, finish fixtures to be determined by owner



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office:
3319 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODEL AND ADU ADDITION FOR
CUONG NGUYEN
1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:
APRIL 23, 2019

Scale:
AS NOTED

COPYRIGHT

THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

DRAWING TITLE:
PROPOSED KITCHEN AND BATH INTERIOR ELEVATIONS

Sheet :
9 OF 10

Page No. :

A. 501

No.	Revision/Issue	Date
1	ISSUED FOR PLANNING APPROVAL	
2		
3		
4		
5		



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office:
3379 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODEL AND ADU ADDITION FOR
CUONG NGUYEN
1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:
APRIL 23, 2019
Scale:


DRAWING TITLE:
3D RENDERS

Sheet :
10 OF 10

Page No. :

A. 601

No.	Revision/Issue	Date
△		
△		
△		
△		



REMODEL AND ADU ADDITION

1651 Parkside Ave.
San Jose
CA 95125

MEP set of plans:

- 1 Cover Cover & List of plans
- 2 M00 HVAC Legend, abbreviations and codes
- 3 M01 HVAC ductworks-1
- 4 M02 HVAC ductworks-2
- 5 M03 HVAC Equip.Details
- 6 M04 Furnace & Heat pump details
- 7 M05 Isometric view
- 8 E00 Electrical Legend and codes
- 9 E01 Appliances & wiring-1
- 10 E02 Appliances & wiring-2
- 11 E03 Lighting circutray and branches-1
- 12 E04 Lighting circutray and branches-2
- 13 E05 Equipment Specifications & Details
- 14 E06 Power riser SLD
- 15 E07 distribution panel details DP-1
- 16 E08 distribution panel details DP-2
- 17 E09 Lights &Photometric studies & FC Levels
- 18 E10 PhotometricPlan-1
- 19 E11 PhotometricPlan-2
- 20 E12 Fire Alarm sensors 1
- 21 E13 Fire Alarm sensors 2
- 22 E14 Lightening protection and Grounding
- 23 E15 Data and CATV -1
- 24 E16 Data and CATV -2
- 25 P00 Piping Codes and Legends
- 26 P01 Plumbing Plan 1
- 27 P02 Plumbing plan 2
- 28 P03 Plumbing SLD 1
- 29 P04 Plumbing SLD 2
- 30 P05 Main House rough-in and Plumbing SLD
- 31 P06 Water Softner & Water meter connection
- 32 P07 Waste Water Plan-1
- 33 P08 Waste Water Plan-2
- 34 P09 Sectional views
- 35 P10 Natural Gas Piping
- 36 P11 Natural Gas Piping SLD and Equip. details
- 37 P12 Roof Drainage plan



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office:
3319 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODLE AND ADU SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:	DRAWING TITLE:	Sheet :
Scale:	-	
COPYRIGHT THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.		Page No. : 00

No.	Revision/Issue	Date
01	*Issued for Planing Approval Rev1.0*	8/18/2019

Space Schedule								
Name	Number	Number of People	Calculated Cooling Load	Calculated Cooling Load per area	Calculated Heating Load	Calculated Heating Load per area	Calculated Supply Airflow	Calculated Supply Airflow per area
Master Bed room	1	2	309 W	1.73 W/ft²	-309 W	-1.73 W/ft²	36.2 ft³/min	0.20 CFM/ft²
Kitchen and Great Room	2	10	4916 W	4.63 W/ft²	3980 W	3.75 W/ft²	575.2 ft³/min	0.54 CFM/ft²
Dining	3	10	575 W	3.59 W/ft²	-575 W	-3.59 W/ft²	67.3 ft³/min	0.42 CFM/ft²
Bed room 2	13	2	1641 W	9.72 W/ft²	2350 W	13.91 W/ft²	192.0 ft³/min	1.14 CFM/ft²
family room	16	2	2438 W	11.51 W/ft²	1128 W	5.32 W/ft²	285.3 ft³/min	1.35 CFM/ft²
Bed room 3	19	2	3521 W	14.64 W/ft²	1670 W	6.94 W/ft²	412.0 ft³/min	1.71 CFM/ft²

STATE OF CALIFORNIA

ALTERATIONS - HVAC

CEC-CF1R-ALT-04-E (Revised 01/16)

CALIFORNIA ENERGY COMMISSION

CERTIFICATE OF COMPLIANCE

CF1R-ALT-04-E

Alterations - HVAC CZ 2, and 8-15

(Page 1 of 1)

Site Address:

Enforcement Agency:

Date Prepared:

Permit#:

Equipment Type

Equipment Efficiency

New Ducting or Lineset: Required R-value

Conditioned Floor Area (ft²)

Thermostat

☐ Packaged System

☐ Split System

☐ Mini Split

☐ Furnace

☐ Evaporator Coil

☐ Condensing Unit

☐ Compressor

☐ Lineset

☐ TXV

_____AFUE

_____SEER

_____EER

_____COP

_____HSPF

☐ R-6 (CZ 1-10, 12&13) Ducts

☐ R-8¹ (CZ 11, 14-16) Ducts

☐ ≥ R-2.8 Lineset⁴

Served by system

_____ft²

☐ Setback (If not already present, must be installed)

HERS VERIFICATION SUMMARY

Installer determines work to be completed and matches to one of the options below. At permit application this form is allowed to be filled out by hand. For final inspection all forms are to be registered (no hand filled forms allowed) and a copy left on site.

☐ 1. HVAC Changeout/Repair

Required Compliance Documents to be left on site for Final:

All Equipment, Condenser Unit, Evaporator Coil, Compressor, TXV, Lineset, Air Handler/Furnace² (Can include new ducting)

CF1R-ALT-02-E
CF2R-MCH-01-E, MCH-20-H, MCH-(23 or 24)²-H, MCH-25-H²
CF3R-MCH-20-H, MCH-(23 or 24)-H², MCH-25-H²

Installer Requirement: Duct leakage ≤ 15%, or ≤ 10% to outside, or seal all accessible leaks), Air Flow ≥ 300 CFM/ton, Refrigerant Charge. Exempted from duct leakage testing if:

☐ 1. Duct system registered with HERS provider as previously sealed, or ☐ 2. There is less than 40 linear feet of duct in unconditioned space, or ☐ 3. Existing duct systems are constructed, insulated or sealed with asbestos (list manufacture date of building _____)

☐ 2. New HVAC System

Required Compliance Documents to be left on site for Final:

All new equipment and All New Ducts³ including Mini Split

CF1R-ALT-02-E
CF2R-MCH-01-E, MCH-20-H, MCH-22-H, MCH-(23 or 24)-H², MCH-25-H²
CF3R-MCH-20-H, MCH-22-H, MCH-(23 or 24)-H², MCH-25-H²
Mini Splits require CF1R-ALT-02-E, CF2R-MCH-01-E, and (CF2R-CF3R) MCH-25-H

Installer Requirement: Duct leakage ≤ 5%, Fan Efficacy (0.58W/CFM), Air Flow ≥ 350 CFM/ton (or alternative), Refrigerant Charge

Exempted from duct leakage testing if: ☐ 1. Existing duct systems are constructed, insulated or sealed with asbestos

☐ 3. All New Ducts with Replacement

Required Compliance Documents to be left on site for Final:

All New Ducts³ and one or more of the following replaced: Condenser Unit, Evaporator Coil, Compressor, TXV, Lineset, Furnace²

CF1R-ALT-02-E
CF2R-MCH-01-E, MCH-20-H, MCH-(23 or 24)-H, MCH-25-H
CF3R-MCH-20-H, MCH-(23 or 24)-H, MCH-25-H

Installer Requirement: Duct leakage ≤ 5%, Air Flow ≥ 350 CFM/ton (or alternative), Refrigerant Charge

Exempted from duct leakage testing if: ☐ 1. Existing duct systems are constructed, insulated or sealed with asbestos

☐ 4. New Ducting over 40 feet

Required Compliance Documents to be left on site for Final:

New ducting but less than All New Ducts³

CF1R-ALT-02-E, CF2R-MCH-20-H, CF3R-MCH-20-H

Installer Required to: Duct leakage (≤ 15% or, ≤ 10% to outside or, or seal all accessible leaks)

☐ EXCEPTION: Existing duct systems constructed, insulated or sealed with asbestos.

¹ All new ducting requires R-8 insulation when more than 40 ft installed in CZs 11 & 14-16 and R-6 in CZs 1-10, 12 & 13, and R-6 insulation when less than 40 ft installed. This includes in walls, between floors etc.

² Heating only systems and Air Handler/Furnace changes do not require Air Flow MCH-(23 or 24), or Refrigerant Charge verification MCH-25

³ All New Ducts is when at least 75% of the duct system is new duct material, and up to 25% may consist of reused parts from the dwelling unit's existing duct system (e.g., register s, grilles, boots, air handler, coil, plenums, duct material)

⁴ R-2.8 (1" thick insulation) for linesets 1" and less.

Contractor (Documentation Author's /Responsible Designer's Declaration Statement)

I certify the following under penalty of perjury, under the laws of the State of California:

1. The information provided on this Certificate of Compliance is true and correct.

2. I am eligible under Division 3 of the California Business and Professions Code to accept responsibility for the information on this document.

3. That the energy features and performance specifications for the design identified on this Certificate of Compliance conform to the requirements of Title 24, Parts 1 and 6 of the California Code of Regulations (CCR).

4. That the energy features and performance specifications, materials, components, and manufactured devices for the building design or system design identified on this Certificate of Compliance conform to the requirements of Title 24, Part 1 and Part 6 of the CCR.

5. The building design features or system design features identified on this Certificate of Compliance are consistent with the information provided on other applicable compliance documents, worksheets, calculations, plans and specifications submitted to the enforcement agency for approval with this building permit application.

Responsible Designer Name:

Responsible Designer Signature:

Date Signed:

License:

Company :

Address:

City/State/Zip:






Phone:

For assistance or questions regarding the Energy Standards, contact the Energy Hotline at: 1-800-772-3300

Building Type	Single Family
Area (SF)	3,246
Volume (CF)	35,292.06
calculated results	
Peak Cooling Total Load (W)	35,517
Peak Cooling Month and Hour	September 3:00 PM
Peak Cooling Sensible Load (W)	35,754
Peak Cooling Latent Load (W)	-237
Maximum Cooling Capacity (W)	35,517
Peak Cooling Airflow (ft³/min)	3,977.20
Peak Heating Load (W)	28,911
Peak Heating Airflow (ft³/min)	3,753.00
Cooling Load Density (W/ft²)	10.94
Cooling Flow Density (CFM/ft²)	1.23
Cooling Flow / Load (CFM/ton)	393.81
Cooling Area / Load (ft²/ton)	321.38
Heating Load Density (W/ft²)	8.91
Heating Flow Density (CFM/ft²)	1.16

1st floor summary	
Area (SF)	2,150
Volume (CF)	21,592.74
Peak Cooling Total Load (W)	7,925
Peak Cooling Month and Hour	July 11:00 AM
Peak Cooling Sensible Load (W)	7,438
Peak Cooling Latent Load (W)	486
Peak Cooling Airflow (ft³/min)	747.5
Peak Heating Load (W)	2,507
Peak Heating Airflow (ft³/min)	842.3
Cooling Load Density (W/ft²)	3.69
Cooling Flow Density (CFM/ft²)	0.35
Cooling Flow / Load (CFM/ton)	331.73
Cooling Area / Load (ft²/ton)	953.93
Heating Load Density (W/ft²)	1.17
Heating Flow Density (CFM/ft²)	0.39

2nd Floor summary	
Area (SF)	1,096
Volume (CF)	13,699.32
Peak Cooling Total Load (W)	27,601
Peak Cooling Month and Hour	September 3:00 PM
Peak Cooling Sensible Load (W)	27,781
Peak Cooling Latent Load (W)	-179
Peak Cooling Airflow (ft³/min)	3,229.70
Peak Heating Load (W)	22,287
Peak Heating Airflow (ft³/min)	2,910.60
Cooling Load Density (W/ft²)	25.18
Cooling Flow Density (CFM/ft²)	2.95
Cooling Flow / Load (CFM/ton)	411.51
Cooling Area / Load (ft²/ton)	139.66
Heating Load Density (W/ft²)	20.33
Heating Flow Density (CFM/ft²)	2.66

	Flex duct
	Diffuser
	Supply Duct
	Exhaust Duct
	Supply Fan
	Setback thermostat
	A/C Liquid line
	A/C Suction line
	Return diffuser
	Return Duct

HVAC ABBREVIATIONS			
A	AMPERES	HZ	FREQUENCY
AC	AIR CONDITIONING	IN	INCH OR INCHES
AD	ACCESS DOOR	KW	KILOWATT
AFF	ABOVE FINISHED FLOOR	LG	LENGTH
AL	ACOUSTICAL LINING	LAT	LEAVING AIR TEMPERATURE
BHP	BRAKE HORSEPOWER	LBS	POUNDS
BTU	BRITISH THERMAL UNIT	LDB	LEAVING DRY BULB TEMPERATURE
BTUH	BTU PER HOUR	LIN FT	LINEAR FEET
CD	CEILING DIFFUSER	LWB	LEAVING WET BULB TEMPERATURE
CFM	CUBIC FEET PER MINUTE	MAX	MAXIMUM
CG	CEILING GRILLE	MBH	THOUSAND BTU PER HOUR
CLG	CEILING	MHP	MOTOR HORSEPOWER
COMPR	COMPRESSOR	MIN	MINIMUM
CR	CEILING REGISTER	NIC	NOT IN CONTRACT
DB	DRY BULB	NO	NUMBER
DIAM	DIAMETER	NTS	NOT TO SCALE
DN	DOWN	RA	RETURN AIR
DWG	DRAWING	RM	ROOM
DX	DIRECT EXPANSION	RPM	REVOLUTIONS PER MINUTE
EAT	ENTERING AIR TEMPERATURE	SP	STATIC PRESSURE
EDB	ENTERING DRY BULB TEMPERATURE	SPEC	SPECIFICATION
EF	EXHAUST FAN	TEMP	TEMPERATURE
EWB	ENTERING WET BULB	TG	TOP GRILLE
EWI	ENTERING WATER TEMPERATURE	TV	TURNING VANES
F	DEGREES FAHRENHEIT	TYP	TYPICAL
FC	FLEXIBLE CONNECTION	W	WIDTH
FD	FIRE DAMPER	W/	WITH
FIN FL	FINISHED FLOOR	W/O	WITHOUT
FLA	FULL LOAD AMPERES	WB	WET BULB
FPM	FEET PER MINUTE	WMS	WIRE MESH SCREEN
FT	FEET	SG	SUPPLY GRILLE
HD	HEAD	RG	RETURN GRILLE
HR	HOUR	SP	SMOKE PURGE
MAU	MAKE UP AIR UNIT		

Notes:

Duct Insulation:

In all cases, unless ducts are enclosed entirely in conditioned space, the minimum allowed duct insulation value is R-6

Thermostats:

Automatic setback thermostats will be installed in the house.

Air Distribution Ducts and Plenums:

air distribution ducts should be sealed and HERS tested for leakage be done by contractor.



PixelArch Ltd.



- US Office:
1442N. Dale Ave. Anaheim, CA 92801
- Canada Office:
3319 Plateau Blvd. Coquitlam BC V3E 3B8
- +1 909 939 2585 info@pixelarchtld.com
www.pixelarchtld.com

Project Name and Address:

REMODE AND ADU SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:	DRAWING TITLE:	Sheet :	No.	Revision/Issue	Date
Scale:	HVAC Legend, abbreviations and codes		01	*Issued for Planing Approval Rev1.0"	8/18/2019
COPYRIGHT THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.		Page No. : M00			



Furnace must be completely sealed to floor or base.
Combustion/ ventilation air supply pipes must terminate 12" from top of closet and 12" from floor of closet. DO NOT remove solid base plate for side return.
Return air ducts must be completely sealed to the furnace and terminate outside the enclosure surfaces.
Unobstructed front clearance of 24" for servicing is recommended.

HVAC ductworks plan - 1st floor

scale : 1 / 4" = 1'

PixelArch Ltd.

US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3313 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMOLDE AND ADU SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

DRAWING TITLE:

Sheet :

No.

Revision/Issue

Date

Scale:


1/4" = 1'-00"

HVAC ductworks

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

Page No. :

M01



HVAC ductworks plan - 2nd floor

scale : 1 / 4" = 1'

PixelArch Ltd.

US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office:
3313 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODLE AND ADU SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

DRAWING TITLE:

Sheet :

Scale:

1/4" = 1'-00"


HVAC ductworks

Page No. :


M02

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.


No.	Revision/Issue	Date



TYPICAL FURNACE UNIT DETAILS FU-1~3
NO SCALE



KITCHEN EXHAUST SYSTEM
SCALE: N.T.S.




Bath- Fan Venting System


AW908 Ducted Ceiling Exhaust Fan
And Duct Kit - Box Grille



FLOOR AIR DIFFUSER /
RECTANGULAR AXIS™ 35BF-V



XC25-060
Air Conditioner



CX35-60D-6F Cooling Coil



SPECIFICATIONS						
General Data		Model No.	XC25-024	XC25-036	XC25-048	XC25-060
		Nominal Tonnage	2	3	4	5
Connections (sweat)	Liquid line (o.d.) - in.		3/8	3/8	3/8	3/8
	Suction line (o.d.) - in.		7/8	7/8	7/8	1-1/8
Refrigerant		¹ R-410A charge furnished	13 lbs. 10 oz.	10 lbs. 12 oz.	14 lbs. 8 oz.	12 lbs. 9 oz.
Outdoor Coil	Net face area - sq. ft.	Outer coil	27.21	27.21	27.21	27.21
		Inner coil	26.36	26.36	26.36	26.36
	Tube diameter - in.	5/16	5/16	5/16	5/16	
		No. of rows	2	2	2	2
	Fins per inch	22	22	22	22	
Outdoor Fan	Diameter - in.	26	26	26	26	
		No. of blades	5	5	5	5
	Motor hp	1/3	1/3	1/3	1/3	
	Cfm - Max. Speed	2925	4100	4220	4385	
	Min. Speed	1950	1950	3020	3020	
		Rpm - Max. Speed	490	650	675	700
	Min. Speed	350	350	500	500	
		Watts - Max. Speed	75	157	185	212
	Min. Speed	32	32	82	82	
Shipping Data - lbs. - 1 pkg.			303	303	330	330

SPECIFICATIONS		Model No.	CX35-49C-6F	CX35-50/60C-6F	CX35-60C-6F	CX35-60D-6F
General Data		Nominal size - Tons	4	4 / 5	5	5
Factory Installed Expansion Valve			12J20	12J20	12J20	12J20
Line Connections in.	Suction / vapor o.d. - sweat		7/8	7/8	7/8	7/8
	Liquid o.d. - sweat		3/8	3/8	3/8	3/8
	Condensate drain (fpt)		(2) 3/4	(2) 3/4	(2) 3/4	(2) 3/4
Shipping Data - lbs.			70	60	73	72

SLP98UH070XV36B Furnace



SPECIFICATIONS		Model No.	SLP98UH070XV36B	SLP98UH090XV36C	SLP98UH090XV48C
Gas Heating Performance	AHRI Reference No.		4792115	4792116	4792117
	¹ AFUE		98.1%	98.1%	98.2%
	Maximum	Input - Btuh	66,000	88,000	88,000
		Output - Btuh	64,000	85,000	85,000
	Temperature rise range - °F		50 - 80	60 - 90	50 - 80
		Gas Manifold Pressure (in. w.g.)	3.5 / 10.0	3.5 / 10.0	3.5 / 10.0
	Minimum	Input - Btuh	23,000	31,000	31,000
		Output - Btuh	22,000	30,000	30,000
	Temperature rise range - °F		35 - 65	35 - 65	35 - 65
		Gas Manifold Pressure (in. w.g.)	0.5 / 1.5	0.5 / 1.5	0.5 / 1.5
Connections in.	High static - in. w.g.		0.8	0.8	0.8
		Intake / Exhaust Pipe (PVC)	2 / 2	2 / 2	2 / 2
	Gas pipe size IPS		1/2	1/2	1/2
		Condensate Drain Trap (PVC pipe) - i.d.	3/4	3/4	3/4
	with furnished 90° street elbow with field supplied (PVC coupling) - o.d.		3/4 slip x 3/4 Mipt	3/4 slip x 3/4 Mipt	3/4 slip x 3/4 Mipt
		Wheel nominal diameter x width - in.	10 x 9	10 x 9	11 x 11
	Motor output - hp		1/2	1/2	3/4
		Tons of add-on cooling	2 - 3	2 - 3.5	2.5 - 4
Electrical Data	Voltage (Maximum Amps)		339 - 1365	520 - 1360	528 - 1770
		Air Volume Range - cfm			
	Blower motor full load amps		7.7	7.7	10.1
Shipping Data	Maximum overcurrent protection		15	15	15
		lbs. - 1 package	138	155	165

NOTE - Filters and provisions for mounting are not furnished and must be field provided.
¹ Annual Fuel Utilization Efficiency based on DOE test procedures and according to FTC labeling regulations. Isolated combustion system rating for non-weatherized furnaces.

PixelArch Ltd.

US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office:
3319 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMOLDE AND ADU SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

DRAWING TITLE:

Sheet :

No.

Revision/Issue

Date



Scale:

HVAC Equip. details

Page No. :

M03



COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.



Type of Elbow Fitting	Inside Diameter (inches)		
	3/4	7/8	1 1/8
90° short radius	1.7	2	2.3
90° long radius	1.5	1.7	1.6
45°	0.7	0.8	1

Installation of Refrigerant Piping

Installation of Refrigerant Piping (Horizontal)




NOTE: For any residential split system installed with a long line set, 3/8" liquid line size must be used.




INSTALLATION GENERAL NOTES:
Clearance space to the structure, wall, or fence Allow at least 12" distance to a wall or fence or similar solid obstruction - typical of most installation instructions.

Clearance distances from an inside corner Inside corner locations on single story structures require evaluation. Large overhanging soffits may cause air recirculation in a corner area even though recommended clearances are maintained. As a guide locate the unit far enough out so that half of the discharge grille is out from under the soffit.

Clearance distances for the compressor/condenser from water, ice, snow : Position so water, snow, or ice from roof or eaves cannot fall directly on unit.



Installation of Refrigeration Piping From Vertical to Horizontal



PixelArch Ltd.
US Office:
1442N. Dale Ave, Anaheim, CA 92801
Canada Office:
3313Plateau Blvd. Coquitlam BC V5E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMOLD AND ADU SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

DRAWING TITLE:

Furnace & Heat pump Details

Sheet :

Page No. :


M04

No.

Revision/Issue

Date

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.



Opening in Stem walls

scale : 1 / 4" = 1'



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3313 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com


Project Name and Address:

REMODLE AND ADU SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:	DRAWING TITLE:	Sheet :
Scale:	stem wall openings	
COPYRIGHT THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.		Page No. : M06

No.	Revision/Issue	Date



Return Air flow plan - 1st floor

scale : 1 / 4" = 1'



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office:
3313 Plateau Blvd. Coquitlam BC V5E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODE AND ADU SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date: _____
Scale: _____
DRAWING TITLE:
return air flow 1st floor
COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

Sheet : _____
Page No. : _____
M07

No.	Revision/Issue	Date



NEC considerations:

210.12Arc–Fault Circuit–Interrupter Protection. Arc fault circuit–interrupter protection shall be provided as required in (210.12A) and (B). The arc–fault circuit interrupter shall be installed in a readily accessible location

(A) Dwelling Units. All –120volt, single phase– 15, and –20ampere branch circuits supplying outlets or devices installed in dwelling unit kitchens, family rooms, dining rooms, living rooms, parlors, libraries, dens, bedrooms, sunrooms, recreation rooms, closets, hallways, laundry areas, or similar rooms or areas shall be protected as described by (1), (2), (3) or (4)

)1(A listed combination type arc–fault circuit interrupter, installed to provide protection of the entire branch circuit.

)2(A listed outlet branch circuit type arc–fault circuit interrupter installed at the first outlet on the branch circuit where all of the following conditions are met:

a. The branch circuit over current protection device shall be a listed circuit breaker having an instantaneous trip not exceeding 300 amperes

b. The branch circuit wiring shall be continuous from the branch circuit overcurrent device to the outlet branch circuit arc–fault circuit interrupter

c. The maximum length of the branch circuit wiring from the branch circuit overcurrent device to the first outlet shall not exceed 15.2m 50(ft) for a 14AWG or 21.3m 70(ft) for a 12AWG conductor– d. The first outlet box in the branch circuit shall be identified .

)1(A listed outlet branch circuit type arc–fault circuit interrupter installed at the first outlet on the branch circuit where the portion of the branch circuit between the branch–circuit overcurrent device and the first outlet is installed using RMC, IMC, EMT, Type MC, or steel armored Type AC cables meeting the requirements of

250.118and using metal outlet and junction boxes.

)2(A listed outlet branch circuit type arc–fault circuit interrupter installed at the first outlet on the branch circuit where the portion of the branch circuit between the branch–circuit overcurrent device and the first outlet is installed using a listed metal or nonmetallic conduit or tubing encased in not less than 50mm 2(in.) of concrete.

TITLE 24 NOTES

1. ALL HIGH EFFICACY LUMINAIRES SHALL BE SWITCHED SEPARATELY FROM LOW EFFICACY LUMINAIRES.
2. HIGH–EFFICACY LUMINAIRES SHALL CONSTITUTE MIN. 50% OF TOTAL WATTAGE IN KITCHEN LIGHTING. ADDITIONAL 50–WATTS OF LOW–EFFICACY LUMINAIRES ARE PERMITTED FOR DWELLING UNIT UNDER 2,500–SF AND ADDITIONAL 100–WATTS ALLOWED FOR OVER 2,500–SF.
3. ALL LOW–EFFICACY KITCHEN LUMINAIRES SHALL BE CONTROLLED BY CEC APPROVED VACANCY SENSOR OR DIMMER.
4. NO MORE THAN 20–WATTER PER LINEAR FOOT OF PERMANENTLY INSTALLED INTERNAL CABINET LIGHTING IS PROHIBITED.
5. ALL LOW–EFFICACY BUILDING MOUNTED EXTERIOR LUMINAIRES SHALL BE CONTROLLED BY PHOTOCELL & MOTION SENSOR.
6. ALL LOW–EFFICACY LUMINAIRES IN BATHROOMS MUST BE CONTROLLED BY CEC APPROVED VACANCY SENSOR OR TIMER.
7. ALL LOW EFFICACY LUMINAIRES LOCATED IN GARAGE, LAUNDRY ROOM, CLOSETS, AND UTILITY ROOMS SHALL BE CONTROLLED BY CEC APPROVED VACANCY SENSOR.
8. ALL LOW EFFICACY LUMINAIRES IN AREAS OTHER THAN THOSE LISTED ABOVE SHALL BE CONTROLLED BY DIMMERS OR CEC APPROVED VACANCY SENSOR.
9. ALL FIXTURES INSTALLED IN INSULATED CEILINGS MUST BE C–RATED & LABELED, AND OF AIR–TIGHT CONSTRUCTION BEARING AN ASTM E283 COMPLIANCE LABEL, AND SHALL BE SEALED WITH A GASKET OR CAULK BETWEEN THE HOUSING AND CEILING.
10. ALL EXHAUST FANS SHALL BE SWITCHES SEPARATELY FROM LUMINAIRES.
11. NO SWITCH SHALL BYPASS DIMMER OR CEC APPROVED VACANCY SENSOR.

IRC Notes :

R314.6 Power source

Smoke alarms shall receive their primary power from the building wiring provided that such wiring is served from a commercial source and shall be equipped with a battery backup. Smoke alarms with integral strobes that are not equipped with battery backup shall be connected to an emergency electrical system. Smoke alarms shall emit a signal when the batteries are low. Wiring shall be permanent and without a disconnecting switch other than as required for overcurrent protection.

R314.7 Fire alarm systems

Fire alarm systems shall be permitted to be used in lieu of smoke alarms and shall comply with Sections R314.7.1 through R314.7.4

R322.1.6 Protection of mechanical, plumbing and electrical systems

Electrical systems, equipment and components; heating, ventilating, air conditioning; plumbing appliances and plumbing fixtures; duct systems; and other service equipment shall be located at or above the elevation required in Section R322.2 or R322.3. If replaced as part of a substantial improvement, electrical systems, equipment and components; heating, ventilating, air conditioning and plumbing appliances and plumbing fixtures; duct systems; and other service equipment shall meet the requirements of this section. Systems, fixtures, and equipment and components shall not be mounted on or penetrate through walls intended to break away under flood loads..

R338.2 Charging In any building or interior area used for charging electric vehicles, electrical equipment shall be installed in accordance with the California Electrical Code.

ARTICLE 625 Electric Vehicle Charging:

625.15 Markings.

The electric vehicle supply equipment shall comply with 625.15(A) through (C).

(A) General. All electric vehicle supply equipment shall be marked by the manufacturer as follows:

FOR USE WITH ELECTRIC VEHICLES

(B) Ventilation Not Required. Where marking is required by 625.29(C), the electric vehicle supply equipment shall be clearly marked by the manufacturer as follows:

VENTILATION NOT REQUIRED

The marking shall be located so as to be clearly visible after installation.

(C) Ventilation Required. Where marking is required by 625.52(B), the electric vehicle supply equipment shall be clearly marked by the manufacturer, “Ventilation Required.” The marking shall be located so as to be clearly visible after installation.

Bedroom - Dormitory	20-30 FC	200-300 lux	0.38
Cafeteria - Eating	20-30 FC	200-300 lux	0.65
Classroom - General	30-50 FC	300-500 lux	1.24
Conference Room	30-50 FC	300-500 lux	1.23
Corridor	5-10 FC	50-100 lux	0.66
Exhibit Space	30-50 FC	300-500 lux	1.45
Gymnasium - Exercise / Workout	20-30 FC	200-300 lux	0.72
Gymnasium - Sports / Games	30-50 FC	300-500 lux	1.2
Kitchen / Food Prep	30-75 FC	300-750 lux	1.21
Laboratory (Classroom)	50-75 FC	500-750 lux	1.43
Laboratory (Professional)	75-120 FC	750-1200 lux	1.81
Library - Stacks	20-50 FC	200-500 lux	1.71
Library - Reading / Studying	30-50 FC	300-500 lux	1.06
Loading Dock	10-30 FC	100-300 lux	0.47
Lobby - Office/General	20-30 FC	200-300 lux	0.9
Locker Room	10-30 FC	100-300 lux	0.75
Lounge / Breakroom	10-30 FC	100-300 lux	0.73
Mechanical / Electrical Room	20-50 FC	200-500 lux	0.95
Office - Open	30-50 FC	300-500 lux	0.98
Office - Private / Closed	30-50 FC	300-500 lux	1.11
Parking - Interior	5-10 FC	50-100 lux	0.19

ELECTRICAL LEGEND		
SYMBOL	DEFINITION	NOTES
	125V OUTLET	20 AMP SINGLE POLE
	110V OUTLET	20 AMP TWO POLE
	110V OUTLET	EQUIPPED WITH GROUND FAULT INTERRUPTER (TAMPER RESISTANT TYPE)
	EXTERIOR WATERPROOF OUTLET	GROUND FAULT INTERRUPTER
	SWITCH	
	Chandelier	
	WALL MOUNTED LIGHT	
	CEILING LIGHT	
	PANEL	
	METER	
	SMOKE DETECTOR	
	CARBON MONOXIDE/ SMOKE DETECTOR COMBO	BATT. BACK-UP W/ HARDWARE SHALL BE A DISTANCE OF NOT LESS THEN 4" FROM WALL
	Exhaust fan JACK	
	Outdoor Fire Alarm	
	Light mounted Fan	
	TELEVISION JACK	
	Countertop Island LIGHT	
NOTES: * LOCATION OF TV JACKS & PHONE OUTLETS & FANS TO BE VERIFIED @ HOMEOWNER PRE-CONSTRUCTION MEETING. * ALL RECEPTACLES IN ALL HABITABLE ROOMS TO BE ARC FAULT PROTECTED PER ELECTRICAL PROVISIONS OF FBCR 5TH EDITION (2011). * BATHROOM EXHAUST FAN TO HAVE MIN. CAPACITY OF 50 CFM INTERMITTENT PER ELECTRICAL PROVISIONS OF SECTION M1507.3 FBCR 5TH EDITION (2011). * LAUNDRY ROOM RECEPTACLE SHALL BE GROUND FAULT CIRCUIT-INTERRUPTER PROTECTION FOR PERSONNEL ON FEEDERS * WIRING METHOD SHALL BE NON METALLIC CABLE PER ELECTRICAL PROVISIONS OF FBCR 5TH ED (2011). * ALL RECEPTACLES TO BE TAMPER- RESISTANT TYPE * ALL WORK TO COMPLY WITH ELECTRICAL PROVISIONS OF THE FBCR 5TH ED (2011).		

Note :

1. All receptacles are TAMPER RESISTANT RECEPTACLES
2. The main disconnect in DP is AFCI
3. receptacles in bathrooms are all GFI type



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3319Plateau Blvd. Coquitlam BC V5E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODLE AND ADU SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

DRAWING TITLE:

Sheet :

Electrical Legend, Notes and NEC Notes

Scale:
1/4" = 1'-00"

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

Page No. :

E00

No.	Revision/Issue	Date

NEC Note for Service conductors

230.24 Clearances

Overhead service conductors shall not be readily accessible and shall comply with 230.24(A) through (E) for services not over 600 volts, nominal.


(A) Above Roofs

Conductors shall have a vertical clearance of not less than 2.5 m (8 ft) above the roof surface. The vertical clearance above the roof level shall be maintained for a distance of not less than 900 mm (3 ft) in all directions from the edge of the roof.

(B) Vertical Clearance for Overhead Service Conductors


Overhead service conductors, where not in excess of 600 volts, nominal, shall have the following minimum clearance from final grade:

- (1) 3.0 m (10 ft) -- at the electrical service entrance to buildings, also at the lowest point of the drip loop of the building electrical entrance, and above areas or sidewalks accessible only to pedestrians, measured from final grade or other accessible surface only for service-drop cables supported on and cabled together with a grounded bare messenger where the voltage does not exceed 150 volts to ground
- (2) 3.7 m (12 ft) -- over residential property and driveways, and those commercial areas not subject to truck traffic where the voltage does not exceed 300 volts to ground
- (3) 4.5 m (15 ft) -- for those areas listed in the 3.7-m (12-ft) classification where the voltage exceeds 300 volts to ground
- (4) 5.5 m (18 ft) -- over public streets, alleys, roads, parking areas subject to truck traffic, driveways on other than residential property, and other land such as cultivated, grazing, forest, and orchard



Appliance plan - First floor

scale : 1 / 4" = 1'




PixelArch Ltd.
US Office: 1442N. Dale Ave. Anaheim, CA 92801
Canada Office: 3313 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:
REMOLD AND ADU SINGLE FAMILY HOUSE
1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date: _____
Scale: 1/4" = 1'-00"
DRAWING TITLE: Appliances & wiring 1st floor
COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

Sheet : _____
Page No. : E01

No.	Revision/Issue	Date



Appliances plan - second floor

scale : 1 / 4" = 1'



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3313Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODLE AND ADU SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

Scale:
1/4" = 1'-00"


DRAWING TITLE:
Appliances Plan 2nd Floor

Sheet :

Page No. :
E02

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

No.	Revision/Issue	Date



Lights Circuit plan - First floor

scale : 1 / 4" = 1'



PixelArch Ltd.

US Office:
1442N. Dale Ave, Anaheim, CA 92801
Canada Office
3313 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMOLD AND ADU SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

DRAWING TITLE:

Lights circuitry Plan 1st floor

Sheet :


Scale:

Page No. :

E03

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

No.	Revision/Issue	Date



Lights Circuit plan - second floor

scale : 1 / 4" = 1'



PixelArch Ltd.
US Office:
1442N. Dale Ave, Anaheim, CA 92801
Canada Office
3313Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODLE AND ADU SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

Scale:
1/4" = 1'-00"

DRAWING TITLE:
Lights circuitry Plan 2nd floor

Sheet :

Page No. :
E04

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

No.	Revision/Issue	Date

Gas fueled tankless water heater sizing For Main House:

people 5 X5 =25 gal/Hr
Dishwasher 1 X 10=10
Laundry Machine 1 X20= 20
Full Bath room 3 X10 = 30

Total Hot water requirement per Hour = 85 gal/Hr
Minimum Flow rate per minute = 1.41 Gal/Minute
Required a water heater to provide 50 degrees of Heat @ minimum 1.5 Gal/Hr
#2 water heater Rheem Model # RTGH-95DVELN-2 will be used in master- Slave connection mode



More Information
SKU RTGH-84XLN-2
MPN RTGH-84XLN-2
Weight 78.0000
Manufacturer Rheem
UPC 20352695143
GTIN 00020352695143
Energy Source Natural Gas
width 18 1/2
Height27 1/2
Flow Rate @ 35 F Rise 8.4 GPM
Flow Rate @ 45 F Rise 6.6 GPM
Flow Rate @ 65 F Rise 4.4
Max Flow Rate GPM 8.4 GPM
Water Connection 3/4 Inch
Max Heating BTU 157,000

Rheem RTGH-84XLN-2 Natural Gas
Condensing Tankless Water Heater




ADU tankless water heater sizing:


people 3 X5 =15 gal/Hr
Dishwasher 1 X 10=10
Laundry Machine 1 X20= 20
Full Bath room 1 X10 = 10

Total Hot water requirement per Hour = 55 gal/Hr
Minimum Flow rate per minute = 1 Gal/Minute
Required a water heater to provide 50 degrees of Heat @ minimum 1 Gal/Hr
A gas water heater Rheem Model # RTGH-84XLN-2 will be used.

24,000 Btu 13 Seer Goodman Single-Zone Mini
Split Air Conditioning System - MSG24CRN1N -
MSG24CRN1W



- 11 FRONT GRILLE
- CLAMPS
- 21 FRONT GRILLE
- 31 FRONT PANEL (M1)
- 41 FAN BLADE (M7, M8)
- 51 FAN MOTOR (M2, M3, M4)
- 61 FAN BRACKET (M1)
- 71 TOP COVER (M1)
- 81 CONDENSER (M4)
- 91 REAR GRILLE (M1)
- 101 LEFT PANEL (M2, M3, M4)
- 111 REAR PANEL (M5, M6)
- 121 RIGHT PANEL (M1)



POWER- SLD



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3313 Plateau Blvd. Coquitlam BC V5E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODLE AND ADU SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

Scale: 1/4" = 1'-00"

DRAWING TITLE:

Power Riser SLD

Sheet :

Page No. : E06

No.	Revision/Issue	Date

PANELBOARD SCHEDULE - "DP-1"																									
MAIN: 350A MCB		1ST FLOOR								VOLTAGE: 208/120				PHASE: 1		WIRE: 3		MOUNTING: SURFACE		AIC: 22,000		S			
CKT #	TRIP POLE	DESCRIPTION	LOAD (KVA)						PHASE		LOAD (KVA)						DESCRIPTION	TRIP POLE	CKT #						
			LTG	REC	MTR	A/C	HTG	KIT	MISC	A	B	LTG	REC	MTR	A/C	HTG				KIT	MISC				
1	20/1	Small Appliances 1		1.80									0.80							ceiling fans	20/1	20			
3	20/1	Small Appliances 2		1.20								2.00								Lights 1	20/1	4			
5	20/1	Small Appliances 3		1.80								2.00								Lights 2	20/1	6			
7	20/1	Small Appliances 4		1.60												0.40				Refrigerator	20/1	8			
9	20/1	Small Appliances 5(Kitchen GFIs)						1.60							1.80					Oven/Cooktop	20/1	10			
11	20/1	Small Appliances 6		1.20												1.20				Laundry Machine	20/1	12			
13	20/1	Small Appliances 7		1.60												1.80						14			
15	20/1	Small Appliances 8		1.60																Dryer Machine	20/ 2	16			
17	20/1	Bath rooms & Kitchen GFIs		1.60																Fire alarm & DATA	20/1	18			
19	20/1	Exterior lghts	1.00									0.10								Gas Water heater control	20/ 1	20			
21	20/1	Extrior Receptacles		1.80									1.44							DishWasher	20/ 1	22			
23	20 /1																					24			
25															7.70					Elec. Car charger	30/2	26			
27	50 /2	AC Heat pump					6.60						1.80							Furnace	20/1	28			
29																						30			
31	30 /2	Garage Door				2.00									7.70					Elec. Car charger	30 /2	32			
33																						34			
35	20 /1	Elec. Fans		0.40																		36			
LIGHTING (KVA):		5.0	1.0	14.2	2.4	6.6	0.0	1.6	0.0		4.0	0.1	4.0	0.0	17.2	3.4	0.0	CONNECTED LOAD (KVA):		54.5					
RECEPTACLES (KVA):		14.3																	DEMAND LOAD (KVA):		50.6				
MOTORS (KVA):		6.4	PHASE A								25.7	247.5													
A/C (KVA):		6.6	PHASE B								28.8	276.9									CONNECTED LOAD (AMPS):		262.2		
HEATING (KVA):		17.2									KVA	AMPS									DEMAND LOAD (AMPS):		243.5		
KITCHEN (KVA):		5.0																							
MISCELLANEOUS (KVA):		0.0																	AMPACITY REQUIRED:		249.5				

NOTES PROVIDE FEED THRU LUG KIT(S)

BREAKERS PROTECTING MULTI-WIRE BRANCH CIRCUITS SHALL BE FIELD-EQUIPPED WITH A MANUALLY OPERATED HANDLE-TIE DEVICE TO ENSURE THAT ALL UNGROUNDED CONDUCTORS ARE SIMULTANEOUSLY DISCONNECTED PER NEC 240.15.

Service panel installation requirements	
Required meter height - 36 to 75 inches above ground	
Required clear space in front of service panel - 30 inches	
wide by 36 inches deep with a minimum headroom clearance	
of 6 feet-6 inches	
Circuit breakers	

18
20
22
24




PANELBOARD SCHEDULE -DP-2																											
MAIN: 250A MCB GR FLOOR										VOLTAGE: 208/120					PHASE:3		WIRE: 4		MOUNTING: SURFACE			AIC: 22000					
CKT #	BKR TYPE	TRIP	POLE	DESCRIPTION	LOAD (KVA)						PHASE		LOAD (KVA)						DESCRIPTION	TRIP	POLE	BKR TYPE	CKT #				
					LTG	REC	MTR	A/C	HTG	KIT	MISC	R	S	LTG	REC	MTR	A/C	HTG						KIT	MISC		
1		20/1		Small Appliances Bed room		1.80								0.08						Outdoor Lights	20/1			2			
3		20/1		EF		0.10								0.22						Lights (Bed room)	20/1			4			
5		20/1		GFI		0.54								0.20						ceiling fans	20/1			6			
7		20/1		Small Appliances Kitchen						1.80				0.24						Lights (Kitchen and Living room)	20/1			8			
9		20/1		Outdoor receptacles		1								0.10						counter top Lights	20/1			10			
11		20/1		Dish washer		1.80												1.20		Laundry Machine	20/1			12			
13				A/C Package #2				2.00													20/1			14			
15		20/ 2																						16			
17		20/ 1		fire alarm sensors													2.00			A/C Package #1	20/ 2			18			
19		20 /1		Small Appliances living room		0.50												4.10			Water heater 1	30 / 2			20		
21		20 /1		Refrig.		0.36																			22		
23		30 /1		Oven/cooktop					1.80										3.80	Dryer Machine	20 /2			24			
25		20 /1		IAQ Fan			0.20																		26		
LIGHTING (KVA):					1	0	2	0	2	2	2	0		1	0	1	2	4	5	0	CONNECTED LOAD (KVA):					21	
RECEPTACLES (KVA):					2																DEMAND LOAD (KVA):					19	
MOTORS, Sump Pumps (KVA):					1							PHASE R	6	59													
A/C (KVA):					4							PHASE S	5	47							CONNECTED LOAD (AMPS):					101	
HEATING (KVA):					6																DEMAND LOAD (AMPS):					89	
KITCHEN (KVA):					7							KVA		AMPS													
MISCELLANEOUS (KVA):					0																AMPACITY REQUIRED:					90	
NOTES: PROVIDE FEED PROVIDE FEED THRU LUG KIT(S). BREAKERS PROTECTING MULTI-WIRE BRANCH CIRCUITS SHALL BE FIELD-EQUIPPED WITH A MANUALLY OPERATED HANDLE-TIE DEVICE TO ENSURE THAT ALL UNGROUNDED CONDUCTORS ARE SIMULTANEOUSLY DISCONNECTED PER NEC 240.15. BREAKER SELECT OVERCURRENT PROTECTION DEVICE SELECTIONS BASED ON EATON CUTLER-HAMMER. OVERCURRENT																											
													EQUALS ALLOWED BY GE, SIEMENS, SQUARE D.														

AMPACITY REQD CALCS									
LIGHTING	1	KVA	X	125	%	=	1 KVA	9	Amps
RECEPTA TOTAL	2	KVA							
1ST	10	KVA	X	100	%	=	2 KVA	17	Amps
REMAIN	0	KVA	X	50	%	=	0 KVA	0	Amps
MOTORS TOTAL	1	KVA	X	100	%	=	0 KVA	0	Amps
LARGEST		KVA	X	125	%	=	1 KVA	10	Amps
REMAIN	1	KVA	X	100	%	=			
A/C	4	KVA	X	100	%	=	4 KVA	33	Amps
HEATING	4	KVA	X	100	%	=	4 KVA	34	Amps
NON-COINCIDENT LOAD		KVA	X	100	%	=	0 KVA	0	Amps
KITCHEN	7	KVA	X	65	%	=	4 KVA	37	Amps
MISCELLANEOUS	0	KVA	X	100	%	=	0 KVA	0	Amps
TOTAL						=	17 KVA	140	Amps

Table 326.80 Ampacity of Type IGS Cable			
Size (kcmil)	Amperes	Size (kcmil)	Amperes
250	119	2500	376
500	168	3000	412
750	206	3250	429
1000	238	3500	445
1250	266	3750	461
1500	292	4000	476
1750	315	4250	491
2000	336	4500	505
2250	357	4750	519

Conductor Size						Current Rating
AWG	CMA	Diameter (mm)	mm ²	Size		
#32	83	0.20	0.03	•		0.3A
#30	101	0.26	0.05	•		0.5A
#28	160	0.32	0.08	•		0.7A
#26	254	0.41	0.13	•		1.0A
#24	404	0.51	0.20	•		2.0A
#22	643	0.64	0.33	•		3.0A
#20	1,020	0.81	0.52	•		5.0A
#18	1,624	1.02	0.82	•		7.0A
#16	2,583	1.29	1.31	•		10.0A
#14	4,106	1.63	2.08	•		20.0A
#12	6,530	2.05	3.31	•		30.0A
#10	10,384	2.59	5.26	•		50.0A

DP-2 with Power meter



Schneider SEA9BN6M Acti 9 250A Three Phase 6 Way Meter Ready Distribution Board




Acti9 iEM3100 Energy Meters
The iME3100 energy measurement counter is used to measure the active energy consumed by single-phase, three-phase or three-phase + neutral type electrical circuits.

Operating voltage: 3 x 100/173 Vac (50/60 Hz) → 3 x 277/480 Vac (50/60 Hz)
Imax: 63 A
IP40 front panel, IP20 casing
Overvoltage and measurement category III, degree of pollution 2
Electromagnetic environmental class: E2
Mechanical environmental class: M1
Operating temperature: -25 → + 55 °C

Design

NEC 700.2 multiple e breakers.

If this pane & A.J. Also If this pane COORDIN/ applicable. schedule.



DP-2 with Power meter



PixelArch Ltd.
US Office: 1442N. Dale Ave, Anaheim, CA 92801
Canada Office: 3319 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMOLD E AND ADU SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

DRAWING TITLE:

Sheet :

No.

Revision/Issue

Date

Scale:

1/4" = 1'-00"

DP-2 schedule and |Calculation

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

Page No. :

E08

Luminaire parts list								
Index	Manufacturer	Luminaire type	Item number	Fitting	Luminous flux	Light loss factor	Connected load	Quantity
1	Verbatim	IN-0302-1-WH		1x52450	1890 lm	0.80	9w	104

#	Name	Parameter	Min	Max	Average	Min/average	Min/max
1	ADU BLDG	Perpendicular illuminance (Adaptive)	8.48 fc	64.3 fc	37.3 fc	0.227	0.132

#	Name	Parameter	Min	Max	Average	Min/average	Min/max
1	GARAGE	Perpendicular illuminance (Adaptive)	8.23 fc	38.8 fc	26.0 fc	0.317	0.212
2	Master Bath room	Perpendicular illuminance (Adaptive)	31.2 fc	56.2 fc	45.6 fc	0.685	0.556
3	Laundry	Perpendicular illuminance (Adaptive)	14.8 fc	35.5 fc	26.5 fc	0.558	0.417
4	Closet #1	Perpendicular illuminance (Adaptive)	11.4 fc	20.8 fc	16.5 fc	0.689	0.548
5	Master Bed room	Perpendicular illuminance (Adaptive)	7.69 fc	33.8 fc	23.2 fc	0.332	0.227
6	Closet #2	Perpendicular illuminance (Adaptive)	0.00 fc	0.000 fc	0.00 fc	/	/
7	Stairs	Perpendicular illuminance (Adaptive)	17.1 fc	42.0 fc	28.2 fc	0.607	0.408
8	Grand Room	Perpendicular illuminance (Adaptive)	9.55 fc	112 fc	50.6 fc	0.189	0.085
9	Bath room	Perpendicular illuminance (Adaptive)	26.0 fc	40.1 fc	33.8 fc	0.767	0.647
10	Mud room	Perpendicular illuminance (Adaptive)	41.8 fc	66.2 fc	56.1 fc	0.744	0.631

#	Name	Parameter	Min	Max	Average	Min/average	Min/max
1	ADU 2nd Floor	Perpendicular illuminance (Adaptive)	0.38 fc	17.4 fc	4.65 fc	0.082	0.022
2	Office	Perpendicular illuminance (Adaptive)	2.57 fc	9.47 fc	5.83 fc	0.441	0.272
3	Closet #1	Perpendicular illuminance (Adaptive)	3.30 fc	8.80 fc	6.08 fc	0.543	0.375
4	Bed room#2	Perpendicular illuminance (Adaptive)	2.34 fc	9.41 fc	6.41 fc	0.365	0.249
5	Bath Room #2	Perpendicular illuminance (Adaptive)	1.85 fc	9.55 fc	5.25 fc	0.353	0.194
6	Family Room	Perpendicular illuminance (Adaptive)	2.76 fc	13.4 fc	10.0 fc	0.275	0.206
7	closet#2	Perpendicular illuminance (Adaptive)	2.12 fc	8.71 fc	6.13 fc	0.346	0.243
8	Corridor	Perpendicular illuminance (Adaptive)	3.20 fc	9.74 fc	7.25 fc	0.441	0.328
9	Bath Room #3	Perpendicular illuminance (Adaptive)	3.68 fc	7.74 fc	6.42 fc	0.574	0.476
10	Bed Room #3	Perpendicular illuminance (Adaptive)	0.69 fc	6.35 fc	3.55 fc	0.194	0.108

GetInLight 5 Inch Flush Mount LED Ceiling Light with ETL Listed, Soft White 3000K, Matte White Finish, IN-0302-1-WH



Brand GetInLight
Part NumberIN-0302-1-WH
Item Weight 9.6 ounces
Product Dimensions 5.4 x 5.4 x 1 inches
Assembled Height 1.02 inches
Assembled Length 5.4 inches
Assembled Width 5.4 inches
Style Modern
Color 3000k(soft White)
ShapeCircular
Material Metal
Finish Matte White
Number of Lights 38
Included Components Wood Screws, Wire Nuts
Voltage 120 volts
Specific Uses Commercial/Residential
Fixture Features Dimmable
Shade Material Plastic
Light Direction Downlight
Power Source AC
Amperage Capacity 2.3 A
Switch Installation Type Embedded
Batteries Included?No
Batteries Required? No
Certification ETL Listed
Type of BulbLED
Luminous Flux 550.00
Wattage 9.00
Wattage 9 watts
Color Temperature 3000 Kelvin
Color Rendering Index (CRI) 90.00

Wall Sconce - 3 Lights - LED - Chrome and Aluminum



Product specifications
Type Wall sconce
Warranty 1-year warranty
Bulb Type Integrated LEDs
Style Contemporary
Collection Ledgo
Component Metal
Finish Chrome and aluminum
Thickness 3" (7.62 cm)
Width 3.5" (8.89 cm)
Length 19" (48.26 cm)
Wattage 3 x 5 W
Quantity per Box Each

6pcs 5 W LED Candle Lights 500 lm E14 CA35 35 LED Beads SMD 2835 Decorative Warm White White 220-240 V 110-130 V / 6 pcs / RoHS



Quantity 6pcs
LED Beads Quantity 35
Light Color White, Warm White
Type LED Candle Lights
Features Decorative
Wattage (W)5
Initial Lumens (lm) 500
Certification CE, RoHS
Color Temperature (k) 3000 6000
Lifetime (H) >50000
Primary ApplicationGarage / Carport, Storage Room / Utility Room, Hallway / Stairwell, Bathroom, Bedroom, Living Room / Dining Room, Kitchen, Children's Room, Home / Office
Bulb Shape CA35
LED Type SMD 2835
Bulb Base E14
What's in the box LED

6-Light Candle-style Chandelier Ambient Light Painted Finishes Metal Candle Style 110-120V / 220-240V Bulb Not Included / E12 / E14



Specifications
Light Information
Type Chandelier
Style Retro
Features Candle Style
Suggested Space Fit Dining Room, Kitchen, Bedroom, Living Room, Hallway
Number of Tier(Tiers) 1
Suggested Room Size 10-15m²
Power (W) 45
Dimensions
Fixture Height (cm) 36
Fixture Width (cm) 61
Chain/Cord Length (cm) 32
Bulb Type LED, Incandescent
Number of Bulb 6-Light
Wattage per Bulb (W) 45
Bulb Base E12 / E14



PixelArch Ltd.
US Office: 1442N. Dale Ave. Anaheim, CA 92801
Canada Office: 3313Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODLE AND ADJ SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

DRAWING TITLE:

Sheet :

No.

Revision/Issue

Date

Scale:




1/4" = 1'-00"

FC Level and Lights specifications

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

Page No. :

E09



Photometric plan- first floor

scale : 1 / 4" = 1'

PixelArch Ltd.

US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office:
3313 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchtld.com
www.pixelarchtld.com

Project Name and Address:

REMOLDE AND ADJ SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

DRAWING TITLE:

Sheet :

No.

Revision/Issue

Date

Scale:

1/4" = 1'-00"




Photometric Plan 1st floor

Page No. :

E10

COPYRIGHT

THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.



Photometric plan - second floor

scale : 1 / 4" = 1'



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office:
3313 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMOLDE AND ADJ SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

DRAWING TITLE:

Sheet :

No.

Revision/Issue

Date

Scale:

1/4" = 1'-00"

Photometric Plan 2nd floor

Page No. :

E11

COPYRIGHT

THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

BRK Electronics First Alert 4120B 120V AC/DC Hardwired with 9V Battery
Backup Ionization Smoke Alarm (Upgraded to 9120B)



BRK 4120B Smoke Alarm AC Powered with Battery Back-up. Designed for the fastest possible installation! If AC power fails, the battery back-up keeps the smoke alarm working.


- Ionization Sensor
- Quick Plug-In Power Connector
- Alarm Indication
- Battery Drawer Lock
- Mounting Bracket Lock
- Swing-Open Battery Door
- Battery Activation Tab
- Battery Back-Up
- AC Power Indicator
- Low Battery Warning "Chirp"
- Missing Battery Tab
- 9V Battery Included

Model # 4120B
Operating Voltage 120V AC 60Hz w/ 9V battery backup (4120B only)
Listing UL Listed to U.S. and Canadian safety standards

Kidde 120V Carbon Monoxide Alarm



Power Source	KD-2100646	KD-9000121
Sensor	120V AC, 9V Battery Backup	120V AC, 9V Battery Backup
Audio Alarm	Electrochemical	Electrochemical
Temp. Range	85dB at 10ft	85dB at 10ft
Humidity Range	40° F to 100° F	40° F to 100° F
Size	5% - 95% relative humidity	5% - 95% relative humidity
Weight	5.75" Diameter x 1.8" Depth	5.75" Diameter x 1.8" Depth
Interconnect Up to 24 Kidde Devices	1 lb	1 lb
	Up to 24 Kidde Devices	



Fire alarm and sensors plan - First floor
scale : 1 / 4" = 1'




PixelArch Ltd.
US Office: 1442N. Dale Ave, Anaheim, CA 92801
Canada Office: 3319 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODLE AND ADJ SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:	DRAWING TITLE:	Sheet :	No.	Revision/Issue	Date
Scale:	Fire Alarm sensors 1st floor				
1/4" = 1'-00"					
COPYRIGHT		Page No. :			
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.		E12			



Fire alarm and sensors plan - second floor

scale : 1 / 4" = 1'



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3313 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODLE AND ADJ SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

Scale:
1/4" = 1'-00"

DRAWING TITLE:

Fire Alarm sensors 2nd floor

Sheet :

Page No. :
E13

No.	Revision/Issue	Date

CEC Notes:
CEC Section 250.50 Grounding Electrode System and Grounding Electrode Conductor
250.50 Grounding Electrode System. All grounding electrodes as described in 250.52(A)(1) through (A)(7) that are present at each building or structure served shall be bonded together to form the grounding electrode system. Where none of these grounding electrodes exist, one or more of the grounding electrodes specified in 250.52(A)(4) through (A)(8) shall be installed and used.
Exception: Concrete-encased electrodes of existing buildings or structures shall not be required to be part of the grounding electrode system where the steel reinforcing bars or rods are not accessible for use without disturbing the concrete.
CEC Section 250.104 Bonding of Piping Systems and Exposed Structural Metal.
(A) Metal Water Piping. The metal water piping system shall be bonded as required in (A)(1), (A)(2), or (A)(3) of this section. The bonding jumper(s) shall be installed in accordance with 250.64 (A), (B), and (E).
(1) General. Meter water piping system(s) installed in or attached to a building or structure shall be bonded to the service equipment enclosure, the grounded conductor at the service, the grounding electrode conductor where of sufficient size, or to the one or more grounding electrodes used. The bonding jumper(s) shall be sized in accordance with Table 250.66 except as permitted in 250.104(A)(2) and (A)(3).


Grounding - Refer to California Electrical Code (CEC) Table 250.66 to size the conductor

If the water piping system is the only grounding source, then a supplemental electrode must be installed.
If using only a single ground rod, a verification document from the contractor stating a resistance to earth of 25 ohms or less at the property is needed prior to final approval
A minimum 5/8" ground rod must be buried at least 8 feet in the ground. Locate the ground rod as close as practicable to the electric service
Bonding the water piping system - Refer to CEC Table 250.122 to size the conductor

If the main water service piping to the house is metallic, accessible bonding must occur within 5 feet of where the water service enters the house.
If the main water service piping is non-metallic, the cold water piping system may be bonded at any accessible location. Piping is commonly bonded at the water heater. The hot and cold water piping systems are effectively bonded together by the brass plumbing mixing valves at tubs and showers, etc. The San Jose accepts a single bond to the cold water piping only; an additional bonding jumper to the hot water piping is not required.
Bonding the gas piping system

If gas appliances are available, the gas piping is bonded via the grounding conductor in the branch circuit to the gas appliances
If the electrical system does not contain equipment grounds, the gas piping system must be bonded externally with a bonding jumper (same as water piping system).
Gas bonding shall only be connected to the house side of the PG&E gas meter.

2 ground rods must be at least 8 feet buried in the ground with minimum of 6 feet apart. When made of iron or steel, the ground rod must be a minimum 5/8" diameter. Listed stainless steel or nonferrous rods may be 1/2" in diameter.
Grounding electrode conductor shall be connected within 5 ft. from the point of entrance to a cold water pipe grounding electrode. (2007 CEC Section 250-30 Item 3)



Grounding Plan

scale : 1 / 4" = 1'



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office:
3313 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODLE AND ADJ SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

DRAWING TITLE:

Sheet :

No.

Revision/Issue

Date

Scale:

1/4" = 1'-00"

Lightning Protection and Ground System


Page No. :

E14

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

TV = TV location (rg6)
PH = phone location (cat6)
DAT = Data location (cat6)
NO = Network Office(3 cat6 /1 rg6)
NP = Network/Phone (2 cat6)
SP = speaker prewire location
SUB = Subwoofer Prewire location
DD = Distribution Device
ADO = Auxiliary Disconnect Outlet
FODB = Fiber Optic Distribution Box

Data, Phone and CATV SLD for Main House



Data, Phone and CATV plan- first floor

scale : 1 / 4" = 1'

Data, Phone and CATV SLD for ADU



PixelArch Ltd.
US Office: 1442N. Dale Ave. Anaheim, CA 92801
Canada Office: 3313 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:
REMOLDLE AND ADJ SINGLE FAMILY HOUSE
1651 PARKSIDE AVE. SAN JOSE, CA 95125



Date:
Scale: 1/4" = 1'-00"

DRAWING TITLE:
Data and CATV plan 1st floor

Sheet :
Page No. :
E15

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

No.	Revision/Issue	Date



CALIFORNIA GENERAL REGULATIONS:

312.0 Protection of Piping, Materials, and Structures

312.1 General

Piping passing under or through walls shall be protected from breakage. Piping passing through or under cinders or other corrosive materials shall be protected from external corrosion in an approved manner. Approved provisions shall be made for expansion of hot water piping. Voids around piping passing through concrete floors on the ground shall be sealed.

312.2 Installation

Piping in connection with a plumbing system shall be so installed that piping or connections will not be subject to undue strains or stresses, and provisions shall be made for expansion, contraction, and structural settlement. No plumbing piping shall be directly embedded in concrete or masonry. No structural member shall be seriously weakened or impaired by cutting, notching, or otherwise, as defined in the California Building Code or California Residential Code.

312.3 Building Sewer and Drainage Piping

No building sewer or other drainage piping or part thereof, constructed of materials other than those approved for use under or within a building, shall be installed under or within 2 feet (610 mm) of a building or structure, or less than 1 foot (305 mm) below the surface of the ground.

312.4 Corrosion, Erosion, and Mechanical Damage

Piping subject to corrosion, erosion, or mechanical damage shall be protected in an approved manner.

312.5 Protectively Coated Pipe

Protectively coated pipe or tubing shall be inspected and tested, and a visible void, damage, or imperfection to the pipe coating shall be repaired in an approved manner.

312.6 Freezing Protection

No water, soil, or waste pipe shall be installed or permitted outside of a building, in attics or crawl spaces, or in an exterior wall unless, where necessary, adequate provision is made to protect such pipe from freezing.

312.7 Fire–Resistant Construction

Piping penetrations of fire–resistance–rated walls, partitions, floors, floor/ceiling assemblies, roof/ceiling assemblies, or shaft enclosures shall be protected in accordance with the requirements of the California Building Code or California Residential Code.

312.8 Waterproofing of Openings Joints at the roof around pipes, ducts, or other appurtenances shall be made watertight by the use of lead, copper, galvanized iron, or other approved flashings or flashing material. Exterior wall openings shall be made watertight. Counterflashing shall not restrict the required internal cross–sectional area of the vent.

407.2.1 Maximum Flow Rate

The maximum flow rate for public lavatory faucets shall not exceed 0.5 gpm at 60 psi (1.9 L/m at 414 kPa).

407.2.1.1 Residential Lavatory Faucets [HCD 1]

The maximum flow rate of residential lavatory faucets shall not exceed 1.2 gallons (4.54 L) per minute at 60 psi. The minimum flow rate of residential lavatory faucets shall not be less than 0.8 gallons (3.03 L) per minute at 20 psi.

407.2.1.2 Lavatory Faucets in Common and Public Use Areas [HCD 1 & HCD 2]

The maximum flow rate of lavatory faucets, installed in common and public use areas (outside of dwellings or sleeping units) in residential buildings, shall not exceed 0.5 gallons (1.89 L) per minute at 60 psi.

RESIDENTIAL WATER & SEWER PIPES

BUILDING INSPECTION REQUIREMENTS

A plumbing permit is required to replace residential water supply piping (main water line from meter to the house), distribution pipes (plumbing within the building), and the sewer system within the building. Permits shall be obtained prior to removal or installation of the plumbing system.

Following is a listing of the general requirements for replacing water and sewer lines based on the 2016 California Plumbing Code, 2016 California Electrical Code, and 2016 California Energy Efficiency Standards. This brochure is intended to provide general information, contact the Building Inspection Division for additional information.

Sewer Line Replacement

•Material for sewer lines outside of the building (minimum 2’outside) can be cast iron, copper type DWV, or schedule 40 DWV ABS/PVC (when used in residential buildings, ABS/PVC is limited to twostory buildings; there is no limit on the number of stories for non–residential buildings). (CPC 701.1, CPC 701.2)

•Clean outs shall be installed at the exterior of the building, within 5’of an underfloor access, at the end of each branch over 5’, at the upper terminal, at each aggregate horizontal change in direction exceeding 135o

, and may be required at the property line by your sanitary district. (CPC 719, 707.4)

•Sewer line shall be 12”below grade minimum and have a minimum of ¼”per one foot slope. (CPC 708) Main Water Supply Line Replacement (Outside the footprint of the building)

•Water supply pipes and fittings shall be PVC, copper (type L or M), malleable iron, galvanized steel, CPVC, or other approved material and shall be in accordance with NSF 61. (CPC 604)

•Underground water lines shall be buried a minimum of 12”below grade. (CPC 609)

•Non–metallic piping shall have a blue insulated 18–guage copper tracer wire adjacent to the piping. The tracer wire shall terminate above ground at each end of the non–metallic pipe. (CPC 604.10.1)

Water Distribution Pipe Replacement (Within and underneath of the building)

•Water distribution pipes shall be copper (Type L or M), malleable iron, galvanized steel, CPVC, PEX, or other approved material and shall be in accordance with NSF 61. (CPC 604)

•All domestic water piping in the following conditions/locations shall be insulated (CEES 150.0(j)2A, CPC 609.11):

The first 5’of cold water pipes from the storage tank (i.e. water heater tank). All domestic hot water piping.

•All materials used in the water distribution system shall be of like materials, except valves and similar devices, unless otherwise approved by the Chief Building Official (CPC 604.1). Following are acceptable methods of joining dissimilar materials:

Joints from copper tubing to threaded pipe shall be made by the use of brass adapter fittings. Dielectric unions shall be used at all point of connection where dissimilar metals are used. Listed

clamps and bonding jumpers shall be installed at all such connections (CEC 250.68(B) and 250.104).

RESIDENTIAL WATER & SEWER PIPES

These requirements apply to building permits submitted on or after January 1, 2017.

When connecting plastic pipe to other types of piping, approved types of fittings and adapters designed for the specific transition shall be used.

•Non–removable backflow preventer, vacuum breaker or atmospheric breaker devices are required on all hose bibs. (CPC 603.5.7)

•If shear walls, braced wall panels, or firewalls are compromised or altered during the re–pipe, these areas are required to be inspected prior to covering.

Grounding and Bonding Requirements

If the existing main water service pipe was used as a grounding electrode, the grounding electrode conductor must be re–established to the replacing pipe. Grounding shall consist of a continuous grounding electrode

conductor run from the panel to a ground rod (grounding electrode) and to the cold water pipe. Grounding of the electrical service at the main water line must be within the first 5’of water piping into the building. The

underground water service shall not be used as the grounding electrode without supplemental electrode. [CEC 250.52 (A)(1) and 250.53 (D)(2), 250.68(C)]

Bonding of all metal piping within the building is required with water service replacements and for all re–pipes. Bonding shall consist of a continuous bond jumper installed at the water heater between the hot, cold, and gas lines, and continued to the main electrical service. (CEC250.4(A)(4))

All Outside piping shall be installed under or within 2 feet (610 mm) of a building or structure, or less than 1 foot (305 mm) below the surface of the ground.

according to CPC.609.11 Pipe Insulation,Insulation of domestic hot water piping shall be in accordance with Section 09.11.1 and Section 609.11.2. of CPC.

609.11.2 Pipe Insulation Wall Thickness. Hot water pipe insulation shall have a minimum wall thickness of

not less than the diameter of the pipe for a pipe up to 2 inches (50 mm) in diameter. Insulation wall thickness

shall be not less than 2 inches (51 mm) for a pipe of 2 inches (50 mm) or more in diameter.

ABBREVIATIONS :

ABBREV.	DESCRIPTION
CO.	CLEAN OUT
DN.	DOWN
FD	FLOOR DRAIN
FCO	FLOOR CLEAN OUT
F.F.L	FINISH FLOOR LEVEL
UG	UNDER GROUND
UT	UNDER TILE
WP	WASTE PIPE
VP	VENT PIPE
VS	VENT STACK
IC	INSPECTION CHAMBER

	Hot Water Pipe line (HWP)
	Cold Water Pipe line (CWP)
	Sewage and waste water line (SWP)
	Valve
	Piping fixtures (Tee, Elbow, ...)
	Compact Water Filtration System
	Coupling Reducing



PixelArch Ltd.

US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3319Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODLE AND ADJ SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

DRAWING TITLE:

Sheet :

Scale:

Plumbing Codes and Legends

COPYRIGHT


THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

Page No. :

P-00

No.	Revision/Issue	Date

code	Item	Drain	elevation	supply	elevation	type
P-1	Hand Sink	2"	+20"	3/4"	+36"	C.W & H.W
P-2	countertop sink	2"	+20"	3/4"	+38"	C.W & H.W
P-3	Range			3/4"	+54"	C.W & H.W
P-4	Dishwasher	2"	+6"	3/4"	+38"	C.W & H.W
P-5	Laundry	2"	+6"	3/4"	+38"	C.W & H.W
P-6	Water Heater			3/4"	+72"	C.W & H.W
P-7	Bath tube	3/4"	+2"	1/2"	+24"	C.W & H.W
P-8	water Closet with Flush Tank	4"	+1"	3/8"	+20"	C.W
P-10	KITCHEN SINK	2"	+20"	3/4"	+36"	C.W & H.W



Water Piping Plan Schematic- first floor

scale : 1 / 4" = 1'



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3313Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

lumbing schematic 1st floor

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

Scale:
1/4" = 1'-00"

DRAWING TITLE:

Water Piping plans

Sheet :


Page No. :

P01

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

No.	Revision/Issue	Date

code	Item	Drain	elevation	supply	elevation	type
P-1	Hand Sink	2"	+ 20"	3/4"	+ 36"	C.W & H.W
P-2	countertop sink	2"	+ 20"	3/4"	+ 38"	C.W & H.W
P-3	Range			3/4"	+ 54"	C.W & H.W
P-4	Dishwasher	2"	+ 6"	3/4"	+ 38"	C.W & H.W
P-5	Laundry	2"	+ 6"	3/4"	+ 38"	C.W & H.W
P-6	Water Heater			3/4"	+ 72"	C.W & H.W
P-7	Bath tube	3/4"	+ 2"	1/2"	+ 24"	C.W & H.W
P-8	water Closet with Flush Tank	4"	+ 1"	3/8"	+ 20"	C.W
P-10	KITCHEN SINK	2"	+ 20"	3/4"	+ 36"	C.W & H.W



Water Piping Plan Schematic- 2nd floor

scale : 1 / 4" = 1'



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3313Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com


Project Name and Address:

REMODLE AND ADJ SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:	DRAWING TITLE:	Sheet :
Scale: 1/4" = 1'-00"	Plumbing Schematic 2nd floor	
COPYRIGHT THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.		Page No. : P02

No.	Revision/Issue	Date



Main House Water Piping SLD



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3313 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com


Project Name and Address:

REMOLDLE AND ADJ SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:	DRAWING TITLE:	Sheet :
Scale:	Plumbing SLD - Main House	
COPYRIGHT THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.		Page No. : P03

No.	Revision/Issue	Date



ADU Water Piping SLD

No.	Revision/Issue	Date

PLUMBING ROUGH-IN SCHEDULE

code	Item	Drain	elevation	supply	elevation	type
P-1	Hand Sink	2"	+ 20"	3/4"	+ 36"	C.W & H.W
P-2	countertop sink	2"	+ 20"	3/4"	+ 38"	C.W & H.W
P-3	Range			3/4"	+ 54"	C.W & H.W
P-4	Dishwasher	2"	+ 6"	3/4"	+ 38"	C.W & H.W
P-5	Laundry	2"	+ 6"	3/4"	+ 38"	C.W & H.W
P-6	Water Heater			3/4"	+ 72"	C.W & H.W
P-7	Bath tube	3/4"	+ 2"	1/2"	+ 24"	C.W & H.W
P-8	water Closet with Flush Tank	4"	+ 1"	3/8"	+ 20"	C.W
P-9	Floor Drain	4"				Waste
P-10	KITCHEN SINK	2"	+ 20"	3/4"	+ 36"	C.W & H.W

Drainage capacities from fixture and their systems (DFU):

Individual Appliance, Appurtenance or Fixture	Minimum Size	Drainage Fixture Unit Values (DFU)	
	(inch)	Private Installations	Public Installations
Bar sink	1 1/2	1	1
Bathroom (water closet, lavatory, bidet and tub or shower)	3	6	-
Bathtub	1 1/2	2	2
Bidet	1 1/4	1	
Bidet	1 1/2	2	
Clothes Washer	2	3	3
Dishwasher, domestic	1 1/2	2	2
Drinking fountain	1 1/4	0.5	0.5
Floor drain	2	2	2
Shower	2	2	2
Laundry tub	1 1/2	2	2
Lavatory	1 1/4	1	1
Bar sink	1 1/2	1	
Kitchen sink, domestic	1 1/2	2	2
Laundry sink	1 1/2	2	2
Service or mop basin	2		3
Urinal	2	2	2
Water closet with gravity tank	3	3	4
Water closet with flushometer tank	3	3	4

Water Supply Fixture Units (WSFU):

Individual Fixtures	Minimum Fixture Branch Pipe Size	Water Supply Fixture Units WSFU	
	(inch)	Private Installations	Public Installations
Bathtub	1/2	4	4
Bathtub with 3/4" fill valve	3/4	10	10
Bidet	1/2	1	
Dishwasher, domestic	1/2	1.5	1.5
Drinking fountain	1/2	0.5	0.5
Hose Bibb	1/2	2.5	2.5
Lavatory	1/2	1	1
Bar sink	1/2	1	2
Clinic fauce sink	1/2	3	
Kitchen sink, domestic	1/2	1.5	1.5
Laundry sink	1/2	1.5	1.5
Service or mop basin	1/2	1.5	3
Washup basin	1/2	2	
Shower head	1/2	2	2
Urinal with flush tank	1/2	2	2
Wash fountain	3/4	4	
Water closet with gravity tank	1/2	2.5	2.5
Water closet with flushometer tank	1/2	2.5	2.5
Water cooler	1/2	0.5	0.5


Maximum Drainage Fixture Units - Stacks and Horizontal Fixture Branches

Maximum Drainage Fixture Units (DFU)					
Pipe Size		Horizontal fixture branch	Stacks less than three stories in height	Stacks more than three stories high	
NPS (inches)	DN (mm)			Total for stack	Total for one story
1 1/2 ⁰⁾	40	3	4	8	2
2 ⁰⁾	50	6	10	24	6
2 1/2 ⁰⁾	65	12	20	42	9
3	80	20 ¹⁾	48 ¹⁾	72 ²⁾	20 ¹⁾
4	100	160	240	500	90
5	125	360	540	1100	200
6	150	620	960	1900	350

0) No water closet permitted

1) Maximum two water closets

2) Maximum six water closets



ABBREVIATIONS :

ABBREV.	DESCRIPTION
CO.	CLEAN OUT
DN.	DOWN
FD	FLOOR DRAIN
FCO	FLOOR CLEAN OUT
F.F.L	FINISH FLOOR LEVEL
UG	UNDER GROUND
UT	UNDER TILE
WP	WASTE PIPE
VP	VENT PIPE
VS	VENT STACK
IC	INSPECTION CHAMBER

Maximum Drainage Fixture Units - Building Drains and Building Drain Branches from Stacks

Maximum Drainage Fixture Units (DFU)			
Pipe Size		Slope (in/ft (cm/m))	
NPS (inches)	DN (mm)	1/4 (2.1)	1/2 (4.2)
2 ⁰⁾	50	21	26
2 1/2 ⁰⁾	65	24	31
3	80	42 ¹⁾	50 ¹⁾
4	100	216	250
5	125	480	575
6	150	840	1000

PixelArch Ltd.

US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3319Plateau Blvd. Coquitlam BC V5E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODLE AND ADJ SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

DRAWING TITLE:

Sheet :

Scale:

1/4" = 1'-00"

Main House Rough-in

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.



Page No. :

P05

No.	Revision/Issue	Date



Water-Softener connection



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3319 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMOLDE AND ADJ SINGLE FAMILY HOUSE


1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date: _____
Scale: _____
DRAWING TITLE:
Water Softner and Meter Connection
COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

Sheet : _____
Page No. : **P06**

No.	Revision/Issue	Date

code	Item	Drain	elevation	supply	elevation	type
P-1	Hand Sink	2"	+20"	3/4"	+36"	C.W & H.W
P-2	countertop sink	2"	+20"	3/4"	+38"	C.W & H.W
P-3	Range			3/4"	+54"	C.W & H.W
P-4	Dishwasher	2"	+6"	3/4"	+38"	C.W & H.W
P-5	Laundry and Dryer	2"	+6"	3/4"	+38"	C.W & H.W
P-6	Water Heater			3/4"	+72"	C.W & H.W
P-7	Bath tube	3/4"	+2"	1/2"	+24"	C.W & H.W
P-8	water Closet with Flush Tank	4"	+1"	3/8"	+20"	C.W
P-10	KITCHEN SINK	2"	+20"	3/4"	+36"	C.W & H.W



Waste Water Piping Plan - first floor

scale : 1 / 4" = 1'



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3313Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:


REMODLE AND ADJ SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:	DRAWING TITLE:	Sheet :
Scale:	Waste Water Plan 1st floor	
COPYRIGHT THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.		Page No. : P07

No.	Revision/Issue	Date

code	Item	Drain	elevation	supply	elevation	type
P-1	Hand Sink	2"	+20"	3/4"	+36"	C.W & H.W
P-2	countertop sink	2"	+20"	3/4"	+38"	C.W & H.W
P-3	Range			3/4"	+54"	C.W & H.W
P-4	Dishwasher	2"	+6"	3/4"	+38"	C.W & H.W
P-5	Laundry	2"	+6"	3/4"	+38"	C.W & H.W
P-6	Water Heater			3/4"	+72"	C.W & H.W
P-7	Bath tube	3/4"	+2"	1/2"	+24"	C.W & H.W
P-8	water Closet with Flush Tank	4"	+1"	3/8"	+20"	C.W
P-10	KITCHEN SINK	2"	+20"	3/4"	+36"	C.W & H.W



Waste Water Piping Plan - 2nd floor

scale : 1 / 4" = 1'



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3313Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:


REMODLE AND ADJ SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125


Date: _____
Scale: _____
DRAWING TITLE:
Waste Water Plan 2nd floor
COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

Sheet :
Page No. :
P08


No.	Revision/Issue	Date



Section-A



Section-B



Section-C

Roof
20' - 0"

Level 2
10' - 0"

Level 1
0' - 0"

Level 04 - T.O. Fnd.


Wall

-4' - 0"

Garage floor

-3' - 10"

Section-A



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3313 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMOLD AND ADU SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

Scale:

DRAWING TITLE:

Sectional Views

Sheet :

Page No. :


P09

No.

Revision/Issue

Date

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.



Natural Gas Piping Plan

scale : 1 / 4" = 1'



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3313 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:
REMODE AND ADU SINGLE FAMILY HOUSE
Natural Gas Piping Plan
1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date: _____
Scale: _____
DRAWING TITLE:
Piping SLD and standards
COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

Sheet : _____
Page No. : **P10**

No.	Revision/Issue	Date


NATURAL GAS PIPE SIZES REGARDING TO TABLE 1216.2(1) SCHEDULE 40 METALLIC PIPE(NFPA 54

ADU	KITCHEN RANGE	171500	156	13	3 / 4"
			0		
PART	APPLIANCES	BTU/h	GAS REQUIRED	LENGTH	PIPE SIZE
A	FURNACE+ KITCHEN RANGE+ CHIMNEY+ W.H+ Dryer	531500	484	24	1 1/2"
B	FURNACE+W.H+ Dryer	299000	272	24	1"

GAS PIPE SUPPORT	
Size of Pipe	Pipe Support Distance
1/2" Tubing	4 feet
1/2" Steel Pipe 5/8" or 3/4"	6 feet
3/4" to 1" Steel Pipe	8 feet
1-1/4" or larger (Horizontal)	10 feet
1-1/4" or larger (Vertical)	Every Floor

GAS PIPE ALLOWABLE MATERIALS		
Pipe Material	Indoor Installation	Outdoor, Above Ground Installation
Galvanized Wrought Iron	Yes	Yes
Galvanized Steel	Yes	Yes
Black Steel	Yes	No
Corrugated Stainless Steel Tubing	Yes	Yes


Sediment Trap (CPC 1212.8)
A sediment traps is required at each water heater, boiler, and furnace, downstream of the appliance shut-off valve and as close to inlet of the equipment as practical.



Building Permit Review
Two inspections are required; a rough plumbing and a final.
The rough plumbing inspection should be scheduled when the new gas lines are installed, before walls are covered, and before the connection is made to the gas service. A pressure test inspection will be done and all testing equipment is to be provided by the permittee. (CPC 1213.3)
The final inspection should be scheduled after all the work has been completed.
Building Permit Application Requirements
A completed Building Permit Application.

Gas Meter Clearance Distances from Building Features	
Building Feature	Minimum Clearance Distance to Gas Meter or Regulator Vent
Gas meter location	Front wall (front presumed facing public access), or within 3 feet of side wall (see corner clearances)
Regulator relief vent distance from any outside building corner	12 inches With this specification met, there are no clearance distance requirements for building features located around the corner from the gas meter. If the regulator relief vent is less than 12" from any outside corner, then the minimum clearances specified in this table must be maintained. Measure as a direct, straight line from the nearest meter set or component to the nearest edge of the building feature "as if using a string"
Gas meter clearances to finish grade (soil surface)	
Bottom of gas meter to finish grade	6 inches
Bottom of gas line shut-off to finish grade	8 inches
Fuel line connection location (at meter top) to finish grade	32 inches to 46 inches depending on gas meter model & meter type (size or capacity)
Landscape features (e.g. shrubs or fences)	3 feet clear to front of meter 2 feet clear to either side of meter
Minimum soil depth or cover over residential gas service line	18 inches - residential 24 inches - commercial 24 inches - snow country 36 inches
Maximum soil depth or cover over gas service line	Depth includes 4 inches of bedding sand under gas line & 6 inches of sand shading over the gas line, & typical excavation trench width of 12 inches.
Gas meter regulator vent clearance distances to building features	
Gas meter regulator vent clearance distance to windows, attic vent, crawl space vent, soffit vent	3 feet in any direction horizontally or vertically to the feature 1 foot to a feature located below
Gas meter regulator vent clearance to electrical devices such as switches, electrical receptacles, power disconnects	3 feet in any direction to the feature
Gas meter regulator vent clearance to building doors or garage doors	3 feet in any direction horizontally or vertically to the feature 1 foot to a feature located below
Gas Meter Clearances to Other Building Features	
Gas meter clearance distance to air conditioner or heat pump (pad mounted) compressor/condenser unit	Three Feet in any direction
Gas meter clearance distance to electrical generator or electrical transformer	
Gas meter clearance distance to open flame barbecue or cooker or to an incinerator or other open flame device	
Gas meter clearance distance to telephone, cable or other communications connection box or terminal	Two Feet in any direction
Gas meter clearance distance to water spigot (hose bibb)	

SEMI-RIGID COPPER TUBING [NFPA 54: TABLE 6.3(f)] ^{2,3}											
GAS: UNDILUTED PROPANE											
INTENDED USE: TUBE SIZING BETWEEN SINGLE OR SECOND STAGE (LOW PRESSURE) REGULATOR AND APPLIANCE											
TUBE SIZE (inch)											
NOMINAL:	K & L:	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	1 3/4	2	
ACR:	ACR:	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	1 3/4	2	
OUTSIDE:	0.375	0.500	0.625	0.750	0.875	1.125	1.375	1.625	1.875	2.125	
INSIDE: ¹	0.305	0.402	0.527	0.652	0.745	0.995	1.245	1.495	1.745	1.995	
LENGTH (feet)	CAPACITY IN THOUSANDS OF BTU PER HOUR										
10	45	93	188	329	467	997	1800	2830	5890		
20	31	64	129	226	321	685	1230	1950	4050		
30	25	51	104	182	258	550	991	1560	3250		
40	21	44	89	155	220	471	848	1340	2780		
50	19	39	79	138	195	417	752	1180	2470		



Gas/Electric Connection: Left or Right
Airflow Direction: Upflow/Horizontal
Circulator Blower: 1/3 HP
Igniter: 110 Volt Silicon Nitride
Vent: 4-inch Diameter
Electrical: 115 VAC, 60 Hz, single phase, 8.1 amps
Shipping Weight: 130 lbs
Dimensions (W x D x H): 14" x 28-3/4" x 33-3/8"

30 in. 3.0 cu. ft. Single Oven Italian Gas Range with True Convection, 5 Burners, LP Gas


Details			
Appliance Type	Gas Range	Cooktop Surface Type	Recessed
Burner Grate Material	Cast Iron	Fuel Type	Gas
Burner No.1 BTU	15500	Ignition Type	Continuous Spark
Burner No.2 BTU	10500	Included	Installation Kit,Propane (LP) Conversion Kit
Burner No.3 BTU	10500	Number of Burners	5
Burner No.4 BTU	7000	Number of Oven Racks	2
Burner No.5 BTU	7000	Number of Rack Positions	6
Capacity of Oven (cu. ft.)	3.0	Oven Cleaning Options	Manual Clean
Color of Cooktop	Stainless Steel	Oven Features	Broiler,Built-In Clock,Built-In Timer,Convection Oven,Hidden Bake Element,Interior Light,LP Convertible,On Indicator Light,Oven Window,Temperature Control,Warming



Goodman 60,000 BTU 80% AFUE Upflow/Horizontal Gas Furnace Model GMS80603AN

	GMS8 0403A"R	GMS8 0603A"R	GMS8 0604B"R	GMS8 0804B"R	GMS8 0805C"R	GMS8 1005C"R	GMS8 1205D"R	GMS8 1405DNC
HEATING CAPACITY								
Input	40,000	60,000	60,000	80,000	80,000	100,000	120,000	140,000
Natural Gas Output	32,000	48,000	48,000	64,000	64,000	80,000	96,000	112,000
LP Gas Output	32,000	48,000	48,000	64,000	64,000	80,000	96,000	112,000
AFUE ¹	80	80	80	80	80	80	80	80
Available AC @ 0.5" ESP	3	3	4	4	5	5	5	5
Temperature Rise Range (°F)	25 - 55	20 - 50	20 - 50	35 - 65	35 - 65	35 - 65	40 - 70	40 - 70
CIRCULATOR BLOWER								
Size (D x W)	10" x 6"	10" x 6"	10" x 8"	10" x 8"	10" x 10"	10" x 10"	11" x 10"	11" x 10"
Horsepower @ 1075 RPM	3/8	3/8	3/8	3/8	3/8	3/8	3/8	3/8
Speed	4	4	4	4	4	4	4	4
Vent Diameter ²	4"	4"	4"	4"	4"	4"	4"	4"
No. of Burners	2	3	3	4	4	5	6	6
ELECTRICAL DATA								
Min. Circuit Ampacity ³	4.8	4.8	8.8	8.8	8.8	8.8	14.7	14.7
Max. Overcurrent Device (amps) ⁴	15	15	15	15	15	15	15	15

Natural Gas Piping SLD -



Natural Gas Piping SLD - specifications and details



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office:
3313Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMOLD AND ADU SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

DRAWING TITLE:

Sheet :

No.

Revision/Issue

Date

Natural Gas SLD and Equip. Details

COPYRIGHT

THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

Page No. :


P11

Total roof area(main roof)= 3029 sq.ft
Rainfall rate = 2.1
pipe size required : 2”

sq. ft. covered per drain= 1150
TWO DRAIN IS REQUIRED FOR MAIN ROOF
Total roof area(main roof)= 792 sq.ft
ONE DRAIN IS ENOUGH FOR ADU ROOF

***For improvement of drainage, the size of pipe
upgraded to 4” and the number of drain pipe
determined regarding the shape of the roof.

Leader / Pipe Size (in.)	Hourly Rainfall (in.)									
	1	1.5	2	2.5	3	4	5	6	7	8
	Total Sq. Ft. Covered Per Drain									
2	2,880	1,920	1,440	1,150	960	720	575	480	410	360
3	8,800	5,860	4,400	3,520	2,930	2,200	1,760	1,470	1,260	1,100
4	18,400	12,700	9,200	7,360	6,130	4,600	3,680	3,070	2,630	2,300
5	34,600	23,050	17,300	13,840	11,530	8,650	6,920	5,765	4,945	4,325
6	54,000	36,000	27,000	21,600	18,000	13,500	10,800	9,000	7,715	6,750
8	116,000	77,400	58,000	46,400	38,660	29,000	23,200	19,315	16,570	14,500



Roof Drainage plan

scale : 1 / 4" = 1'



PixelArch Ltd.
US Office:
1442N. Dale Ave. Anaheim, CA 92801
Canada Office
3319 Plateau Blvd. Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODLE AND ADU SINGLE FAMILY HOUSE

1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date: _____
Scale: _____
DRAWING TITLE:
Roof Drainage Plan and calculation

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD. PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION WITH OWNER, PIXELARCH LTD.

Sheet :

Page No. :
P12

No.	Revision/Issue	Date

SHEAR WALL SCHEDULE 2016 C.B.C.						
S.W. TYPE	SHEAR PANEL DESCRIPTION	ALLOWABLE SHEAR (PLF)	SILL BOLT'G @ FOUNDATION	TOP PL. TO BL'G.	SILL NAILING UPPER STORIES	
	7/8" STUCCO OVER PAPER BACKED LATH W/ 16 GA STAPLES AT 6" O.C. AT TOP & BOTTOM PLATES, EDGE OF SHEAR WALL AND ON FIELD (CBC TABLE 2306.4.5) SEE NOTE 3 BELOW.	180 *180	5/8" @ 48" O.C. 5/8" @ 24" O.C.	A35 @ 16" A35 @ 16"	16d @ 8" O.C. 16d @ 4" O.C.	
	15/32" APA RATED PLYWOOD SHT'G. STRUCT I WITH 8d COMMON NAILS @ 6" O.C. AT EDGES & 12" O.C. FIELD (TABLE 2306.4.1 CBC) SEE NOTES 1,2,8,9, AND 10 BELOW.	280 *560	5/8" @ 32" O.C. 5/8" @ 16" O.C.	A35 @ 16" A35 @ 8"	16d @ 6" O.C. 16d @ 3" O.C.	
	15/32" APA RATED PLYWOOD SHT'G. STRUCT I WITH 8d COMMON NAILS @ 4" O.C. AT EDGES & 12" O.C. FIELD (TABLE 2306.4.1. CBC) SEE NOTES 1,2,4,5,8,9, AND 10 BELOW.	430 *860	5/8" @ 24" O.C. 5/8" @ 14" O.C.	A35 @ 8" LTP4 @ 6"	16d @ 4" O.C. 16d @ 2" O.C.	
	15/32" APA RATED PLYWOOD SHT'G. STRUCT I WITH 8d COMMON NAILS @ 3" O.C. AT EDGES & 12" O.C. FIELD (TABLE 2306.4.1. CBC) SEE NOTES 1,2,4,5,8,9, AND 10 BELOW.	550 *1100	5/8" @ 20" O.C. 3/4" @ 16" O.C.	A35 @ 8" LTP4 @ 6"	16d @ 3" O.C. 1/4"Ø X 3-1/2" LAG SC. @ 2" O.C.	
	15/32" APA RATED PLYWOOD SHT'G. STRUCT I WITH 8d COMMON NAILS @ 2" O.C. AT EDGES & 12" O.C. FIELD (TABLE 2306.4.1. CBC) SEE NOTES 1,2,4,5,8,9, AND 10 BELOW.	730 *1460	5/8" @ 16" O.C. 3/4" @ 16" O.C.	A35 @ 8" LTP4 @ 6"	16d @ 2-1/2" O.C. 1/4" Ø X 3-1/2" LAG SC. @ 2" O.C.	
	15/32" APA RATED STRUCT. I SHT'G. WITH 10d COMMON NAILS @ 2" O.C. AT EDGES & 12" O.C. FIELD OVER 3 X STUDS (TABLE 2306.4.1 CBC) SEE NOTES 1,4,5,8,9, AND 10 BELOW.	870 *1740	3/4" @ 16" O.C. 3/4" @ 8" O.C.	A35 @ 6" LTP4 @ 4-1/2"	#12 X 3-1/2" WD. SC. @ 2" O.C. 1/4" Ø X 3-1/2" LAG SC. @ 1-1/2" O.C.	

NOTES:

- ALL EDGES OF PLYWOOD SHEAR WALLS MUST BE BLOCKED WITH 2X SOLID BLOCKING.
- DESIGNATES SILL BOLTING OR NAILING WHERE SHEAR WALL PANELS ARE TO BE APPLIED TO BOTH SIDES OF WALL.
- PAPER BACKED SELF-FURRING EXPANDED METAL OR WOVEN WIRE LATH AND PORTLAND CEMENT PLASTER.
- FRAMING AT ADJOINING PANEL EDGES SHALL BE 3-INCH NOMINAL OR WIDER AND NAILS SHALL BE STAGGERED. (USE 3X SILL PLATE @ FOUND. FOR SHEAR LOADS LESS THAN 350 PLF 2X SILL PLATE MAY BE USED.)
- WHERE PANELS ARE APPLIED ON BOTH FACES OF A WALL AND NAILS SPACING IS LESS THAN 6" O.C. ON EITHER SIDE, PANEL JOINTS SHALL BE OFFSET TO FALL ON DIFFERENT FRAMING MEMBERS OR FRAMING SHALL BE 3" NOMINAL OR THICKER & NAILS ON EACH SIDE SHALL BE STAGGERED. (USE 3 X SILL PLATE @ FOUND.)
- ALL CONTINUOUS EXTERIOR AND INTERIOR SHEAR/BEARING WALL FOOTINGS TO HAVE 5/8"Ø A.B.'S @ 48" O.C. WITH 3" X 3" X 1/4" PLATE WASHERS U.N.O.
- ALL INTERIOR NON-BEARING FTGS TO HAVE 3/16" Ø SHOT PINS AT 32" O.C., I.E. HLTI SHOT PINS (ICC ESR-1663).
- USE APA RATED PLYWOOD SHEATHING, OR O.S.B. PANEL. ALL PLYWOOD SHALL BE DOUGLAS FIR, 4-PLY MIN. OTHER SPECIES MAY REQUIRE CHANGES.
- USE 3 X 3 X 1/4 PLATE WASHERS WITH 5/8"Ø A.B. AT ALL SHEAR WALLS. USE 3 X 3 X 5/16 PLATE WASHERS WITH 3/4"Ø A.B. AT ALL SHEAR WALLS.
- AT EXISTING FOOTINGS, USE THREADED RODS W/ SIMPSON "SET-XP" EPOXY 7" MIN. EMB. W/ MIN. EDGE DIST. OF 1-7/8" (ICC ESR-2508) (SPECIAL INSPECTION REQ'D.)
- ALL ANCHOR BOLTS SHALL CONFORM TO ASTM A-307 U.N.O.

12. ANCHOR BOLT SPEC.:

	BOLT LENGTH	
	SINGLE POUR	DOUBLE POUR
2X SILL	12"	16"
3X SILL	14"	18"

SHEAR WALL SCHEDULE

APPLICABLE DESIGN LOADS PER ASG/SEI 7-10

FLOOR LIVE LOAD: 40 PSF

ROOF DEAD LOAD: 20 PSF

BASIC WIND SPEED: 110 MPH

STRUCTURAL CATEGORY: II

ALL PRESSURES SHOWN ARE BASED ON ASD DESIGN.

GENERAL NOTES:

1. CONTRACTOR TO ASSUME FULL RESPONSIBILITY FOR ABIDING TO ALL APPLICABLE CALIFORNIA BUILDING CODES, LOCAL CITY ORDINANCES, ZONING REQUIREMENTS, AND LICENSING/PERMIT REQUIREMENTS. CONTRACTOR IS FULLY RESPONSIBLE FOR ALL CONSTRUCTION MEANS, METHODS, TECHNIQUES, REQUIREMENTS OR PROCEDURES INCLUDING WITHOUT LIMITATION TO DEMOLITION, EXCAVATION AND ERECTION PROCEDURES.

2. THE CONTRACTOR SHALL EXAMINE THE CONSTRUCTION DOCUMENTS AND NOTIFY THE PROJECT ENGINEER & ARCHITECT OF ANY DISCREPANCIES, ERRORS, OR OMISSIONS SHE/HI MAY FIND BEFORE PROCEEDING WITH THE WORK.

3. NOTIFY THE PROJECT ENGINEER OF ANY DESIGN CHANGES PROPOSED BY OWNER OR THE CONTRACTOR DURING THE COURSE OF CONSTRUCTION. SUCH CHANGES AFFECTING ROOM ADDITION DESIGN MAY ALSO AFFECT STRUCTURAL DESIGN.

4. ANY SUBCONTRACTOR WHICH AGREES TO CONSTRUCT THE PROJECT PURSUANT TO THESE PLANS FULLY ASSUMES THE RISK OF ALL ERRORS AND OMISSIONS WHICH SHOULD HAVE BEEN DETECTED BY A CAREFUL REVIEW BY A KNOWLEDGEABLE LICENSED CONTRACTOR, THAT INWHICH FOR ANY REASON WERE NOT RESOLVED DURING THE BIDDING OR NEGOTIATION PROCESS. FURTHER, THE CONTRACTOR SHALL CAREFULLY REVIEW THESE PLANS AS THE WORK PROGRESSES IN ORDER TO IDENTIFY ANY SIGNIFICANT ERRORS AND OMISSIONS AND TO ASCERTAIN ALL NECESSARY INFORMATION BEFORE PROCEEDING WITH THE AFFECTED WORK, AND ASSUMES THE RISK OF ANY AND ALL LOSS, INCLUDING DELAY, WHICH MAY BE CAUSED OR CONTRIBUTED TO BY THE FAILURE TO ASCERTAIN CORRECT OR NECESSARY INFORMATION IN A TIMELY MANNER.

5. ALL TRADES SHALL, AT ALL TIMES, KEEP THE PREMISES FREE FROM ACCUMULATION OF WASTE MATERIALS OR RUBBISH CAUSED BY THEIR WORK, AND AT THE COMPLETION OF THE WORK SHALL REMOVE ALL RUBBISH FROM AND ABOUT THE JOBSITE AND ALL THEIR TOOLS, SCAFFOLDING AND SURPLUS MATERIALS, AND SHALL LEAVE THE JOB BROOM CLEAN, INCLUDING REMOVING ALL LABELS, STICKERS, PAINT SMEARS, ETC., FROM LIGHTING FIXTURES, PLUMBING FIXTURES, GLASS SURFACES, FINISH HARDWARE, CABINETS, COUNTERTOPS, ETC.

6. EXCEPT WHERE MORE STRINGENT REQUIREMENTS ARE NOTED OR SHOWN ON THE PLANS, WORKMANSHIP & MATERIALS SHALL CONFORM TO THE LATEST EDITION OF THE C.B.C. OR LOCAL CODE.

7. THE PLANS SHALL BE REVIEWED FOR DIMENSIONAL & EXISTING SITE CONFORMANCE WITH THE PLANS BY THE CONTRACTOR PRIOR TO THE START OF CONSTRUCTION. THE ARCHITECT & ENGINEER SHALL BE NOTIFIED OF ANY DISCREPANCIES.

8. THE CONTRACTOR SHALL VERIFY ALL CONDITIONS AND DIMENSIONS IN THE FIELD AND ALL QUESTIONS AS TO DIMENSIONS AND FIELD CONDITIONS SHALL BE RESOLVED BEFORE THE AFFECTED WORK PROCEEDS. NO DIMENSIONS SHALL BE OBTAINED BY SCALING THESE PLANS.

9. CONTRACTORS SHALL VERIFY AND BE RESPONSIBLE FOR DIMENSIONS AND CONDITIONS OF THE JOB.

10. THE PRECISE DIMENSIONS AND LOCATIONS OF ALL DOOR, WINDOW AND ROOF OPENINGS SHALL BE DETERMINED FROM DRAWINGS AND OTHER FLOOR, WALL OPENING REQUIRED BY MECHANICAL OR ELECTRICAL SHALL BE VERIFIED FROM SHOP DRAWINGS, EQUIPMENT DATA SHEETS, ETC. AS REQUIRED.

11. ITEMS IDENTIFIED BY TRADE NAMES MAY BE SUBSTITUTED BY APPROVED EQUIVLS.

12. NOTES & DETAILS ON DRAWINGS SHALL PRECEDE THESE GENERAL NOTES.

13. PROVIDE ANY SHORING & OR BRACING PRIOR TO REMOVING EXISTING WALLS, BEAMS, OR SUPPORTS FOR CONSTRUCTION. REMOVE SHORING ONLY WHEN NEW SUPPORTS ARE IN PLACE AND SECURED.

14. PROVIDE RE-HEADS INTO EXISTING CONCRETE AT ALL SHEAR WALLS PER UFG, SPECIFICATIONS. SEE SHEAR WALL SCHEDULE FOR SIZE AND SPACING.

15. PROVIDE SIMPSON ST-6224 BETWEEN NEW WALLS AND EXISTING WALLS AT THE DOUBLE TOP PLATE.

16. THE CONTRACTOR SHALL LOCATE ALL EXISTING UTILITIES WHETHER OR NOT SHOWN ON DRAWINGS AND PROTECT THEM FROM DAMAGE.

17. DO NOT CUT OUT TOP TENSION SLABS. CONTRACTOR TO DETERMINE EXISTING CONDITIONS PRIOR TO START OF CONSTRUCTION.

18. THE CONTRACTOR SHALL VERIFY ALL EXISTING CONDITIONS FOR FOOTING, BEAMS AND JOISTS, SIZES, LOCATIONS, ETC. AND SHALL NOTIFY THE ARCHITECT & ENGINEER OF ANY DISCREPANCIES.

19. DOWEL NEW INTO EXISTING SLABS W/ #4 REBAR @ 24" O.C. AND FOOTINGS W/ DOWELS TO MATCH NEW REINF. SIZE/ LOCATION.

ENGINEERING NOTES

1. CONCRETE SLABS ON GRADE HAVE NOT BEEN DESIGNED BY THE STRUCTURAL ENGINEER.

2. THE VIBRATIONAL EFFECTS OF MECHANICAL EQUIPMENT HAVE NOT BEEN CONSIDERED BY THE STRUCTURAL ENGINEER.

3. THE DESIGN, ADEQUACY AND SAFETY OF ERECTION, BRACING, SHORING, TEMPORARY SUPPORTS ETC., IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR, AND HAS NOT BEEN CONSIDERED BY THE STRUCTURAL ENGINEER. THE CONTRACTOR IS RESPONSIBLE FOR THE STABILITY OF THE STRUCTURE DURING THE ENTIRE COURSE OF CONSTRUCTION. THE ENGINEER SHALL NOT BE HELD RESPONSIBLE FOR FIELD INSPECTION/OBSERVATION OF THE ABOVE ITEMS.

4. ALLOWABLE SOILS PRESSURE TO BE A MINIMUM OF 1500 PSF UNLESS A SOILS REPORT IS PROVIDED. SOILS IN THE BUILDING AREA 4.5 FEET BEYOND SHALL BE COMPACTED TO A MINIMUM OF 90% RELATIVE COMPACTION PER 2016-C.B.C.

REFER TO SOIL REPORT BY: _____

JOB NUMBER: _____

DATED: _____

STRUCTURAL SYMBOLS

INDICATES SHEAR WALL, SEE FOUNDATION, FRAMING PLAN AND SHEAR WALL SCHEDULE FOR TYPE, SILL BOLTING, SHGT, ETC. NOTE FOR SILL BOLTING AT EXISTING FOOTINGS, USE 5/8" Ø THREADED RODS W/ SIMPSON "SET-XP" EPOXY 7' MIN. EMB. PER ICC ESR-2508 THE SAME SIZE & SPACING AS CALLED FOR ON PLANS

INDICATES POST (BELOW BEAM)

MIN. POST SIZE/TYPE AS FOLLOWS U.N.O.:

BEAM SIZE	POST SIZE
4 X 12 & SMALLER	2 X 4 W/ 16d NAILS @ 12" O.C.
4 X 14 & LARGER	4 X 4
6 X 10 & SMALLER	4 X 6
6 X 12 & LARGER	6 X 6

FRAMING FOR FURTHER POST SIZE REQUIREMENTS. POSTS ARE TO CONTINUE DOWN TO FOUNDATION.

DESIGN DATA:

APPLICABLE DESIGN LOADS PER ASG/SEI 7-10

FLOOR LIVE LOAD: 40 PSF

ROOF DEAD LOAD: 20 PSF

BASIC WIND SPEED: 110 MPH

STRUCTURAL CATEGORY: II

ALL PRESSURES SHOWN ARE BASED ON ASD DESIGN.

GENERAL NOTES:

1. CONTRACTOR TO ASSUME FULL RESPONSIBILITY FOR ABIDING TO ALL APPLICABLE CALIFORNIA BUILDING CODES, LOCAL CITY ORDINANCES, ZONING REQUIREMENTS, AND LICENSING/PERMIT REQUIREMENTS. CONTRACTOR IS FULLY RESPONSIBLE FOR ALL CONSTRUCTION MEANS, METHODS, TECHNIQUES, REQUIREMENTS OR PROCEDURES INCLUDING WITHOUT LIMITATION TO DEMOLITION, EXCAVATION AND ERECTION PROCEDURES.

2. THE CONTRACTOR SHALL EXAMINE THE CONSTRUCTION DOCUMENTS AND NOTIFY THE PROJECT ENGINEER & ARCHITECT OF ANY DISCREPANCIES, ERRORS, OR OMISSIONS SHE/HI MAY FIND BEFORE PROCEEDING WITH THE WORK.

3. NOTIFY THE PROJECT ENGINEER OF ANY DESIGN CHANGES PROPOSED BY OWNER OR THE CONTRACTOR DURING THE COURSE OF CONSTRUCTION. SUCH CHANGES AFFECTING ROOM ADDITION DESIGN MAY ALSO AFFECT STRUCTURAL DESIGN.

4. ANY SUBCONTRACTOR WHICH AGREES TO CONSTRUCT THE PROJECT PURSUANT TO THESE PLANS FULLY ASSUMES THE RISK OF ALL ERRORS AND OMISSIONS WHICH SHOULD HAVE BEEN DETECTED BY A CAREFUL REVIEW BY A KNOWLEDGEABLE LICENSED CONTRACTOR, THAT INWHICH FOR ANY REASON WERE NOT RESOLVED DURING THE BIDDING OR NEGOTIATION PROCESS. FURTHER, THE CONTRACTOR SHALL CAREFULLY REVIEW THESE PLANS AS THE WORK PROGRESSES IN ORDER TO IDENTIFY ANY SIGNIFICANT ERRORS AND OMISSIONS AND TO ASCERTAIN ALL NECESSARY INFORMATION BEFORE PROCEEDING WITH THE AFFECTED WORK, AND ASSUMES THE RISK OF ANY AND ALL LOSS, INCLUDING DELAY, WHICH MAY BE CAUSED OR CONTRIBUTED TO BY THE FAILURE TO ASCERTAIN CORRECT OR NECESSARY INFORMATION IN A TIMELY MANNER.

5. ALL TRADES SHALL, AT ALL TIMES, KEEP THE PREMISES FREE FROM ACCUMULATION OF WASTE MATERIALS OR RUBBISH CAUSED BY THEIR WORK, AND AT THE COMPLETION OF THE WORK SHALL REMOVE ALL RUBBISH FROM AND ABOUT THE JOBSITE AND ALL THEIR TOOLS, SCAFFOLDING AND SURPLUS MATERIALS, AND SHALL LEAVE THE JOB BROOM CLEAN, INCLUDING REMOVING ALL LABELS, STICKERS, PAINT SMEARS, ETC., FROM LIGHTING FIXTURES, PLUMBING FIXTURES, GLASS SURFACES, FINISH HARDWARE, CABINETS, COUNTERTOPS, ETC.

6. EXCEPT WHERE MORE STRINGENT REQUIREMENTS ARE NOTED OR SHOWN ON THE PLANS, WORKMANSHIP & MATERIALS SHALL CONFORM TO THE LATEST EDITION OF THE C.B.C. OR LOCAL CODE.

7. THE PLANS SHALL BE REVIEWED FOR DIMENSIONAL & EXISTING SITE CONFORMANCE WITH THE PLANS BY THE CONTRACTOR PRIOR TO THE START OF CONSTRUCTION. THE ARCHITECT & ENGINEER SHALL BE NOTIFIED OF ANY DISCREPANCIES.

8. THE CONTRACTOR SHALL VERIFY ALL CONDITIONS AND DIMENSIONS IN THE FIELD AND ALL QUESTIONS AS TO DIMENSIONS AND FIELD CONDITIONS SHALL BE RESOLVED BEFORE THE AFFECTED WORK PROCEEDS. NO DIMENSIONS SHALL BE OBTAINED BY SCALING THESE PLANS.

9. CONTRACTORS SHALL VERIFY AND BE RESPONSIBLE FOR DIMENSIONS AND CONDITIONS OF THE JOB.

10. THE PRECISE DIMENSIONS AND LOCATIONS OF ALL DOOR, WINDOW AND ROOF OPENINGS SHALL BE DETERMINED FROM DRAWINGS AND OTHER FLOOR, WALL OPENING REQUIRED BY MECHANICAL OR ELECTRICAL SHALL BE VERIFIED FROM SHOP DRAWINGS, EQUIPMENT DATA SHEETS, ETC. AS REQUIRED.

11. ITEMS IDENTIFIED BY TRADE NAMES MAY BE SUBSTITUTED BY APPROVED EQUIVLS.

12. NOTES & DETAILS ON DRAWINGS SHALL PRECEDE THESE GENERAL NOTES.

13. PROVIDE ANY SHORING & OR BRACING PRIOR TO REMOVING EXISTING WALLS, BEAMS, OR SUPPORTS FOR CONSTRUCTION. REMOVE SHORING ONLY WHEN NEW SUPPORTS ARE IN PLACE AND SECURED.

14. PROVIDE RE-HEADS INTO EXISTING CONCRETE AT ALL SHEAR WALLS PER UFG, SPECIFICATIONS. SEE SHEAR WALL SCHEDULE FOR SIZE AND SPACING.

15. PROVIDE SIMPSON ST-6224 BETWEEN NEW WALLS AND EXISTING WALLS AT THE DOUBLE TOP PLATE.

16. THE CONTRACTOR SHALL LOCATE ALL EXISTING UTILITIES WHETHER OR NOT SHOWN ON DRAWINGS AND PROTECT THEM FROM DAMAGE.

17. DO NOT CUT OUT TOP TENSION SLABS. CONTRACTOR TO DETERMINE EXISTING CONDITIONS PRIOR TO START OF CONSTRUCTION.

18. THE CONTRACTOR SHALL VERIFY ALL EXISTING CONDITIONS FOR FOOTING, BEAMS AND JOISTS, SIZES, LOCATIONS, ETC. AND SHALL NOTIFY THE ARCHITECT & ENGINEER OF ANY DISCREPANCIES.

19. DOWEL NEW INTO EXISTING SLABS W/ #4 REBAR @ 24" O.C. AND FOOTINGS W/ DOWELS TO MATCH NEW REINF. SIZE/ LOCATION.

ENGINEERING NOTES

1. CONCRETE SLABS ON GRADE HAVE NOT BEEN DESIGNED BY THE STRUCTURAL ENGINEER.

2. THE VIBRATIONAL EFFECTS OF MECHANICAL EQUIPMENT HAVE NOT BEEN CONSIDERED BY THE STRUCTURAL ENGINEER.

3. THE DESIGN, ADEQUACY AND SAFETY OF ERECTION, BRACING, SHORING, TEMPORARY SUPPORTS ETC., IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR, AND HAS NOT BEEN CONSIDERED BY THE STRUCTURAL ENGINEER. THE CONTRACTOR IS RESPONSIBLE FOR THE STABILITY OF THE STRUCTURE DURING THE ENTIRE COURSE OF CONSTRUCTION. THE ENGINEER SHALL NOT BE HELD RESPONSIBLE FOR FIELD INSPECTION/OBSERVATION OF THE ABOVE ITEMS.

4. ALLOWABLE SOILS PRESSURE TO BE A MINIMUM OF 1500 PSF UNLESS A SOILS REPORT IS PROVIDED. SOILS IN THE BUILDING AREA 4.5 FEET BEYOND SHALL BE COMPACTED TO A MINIMUM OF 90% RELATIVE COMPACTION PER 2016-C.B.C.

REFER TO SOIL REPORT BY: _____

JOB NUMBER: _____

DATED: _____

STRUCTURAL SYMBOLS

INDICATES SHEAR WALL, SEE FOUNDATION, FRAMING PLAN AND SHEAR WALL SCHEDULE FOR TYPE, SILL BOLTING, SHGT, ETC. NOTE FOR SILL BOLTING AT EXISTING FOOTINGS, USE 5/8" Ø THREADED RODS W/ SIMPSON "SET-XP" EPOXY 7' MIN. EMB. PER ICC ESR-2508 THE SAME SIZE & SPACING AS CALLED FOR ON PLANS

INDICATES POST (BELOW BEAM)

MIN. POST SIZE/TYPE AS FOLLOWS U.N.O.:

BEAM SIZE	POST SIZE
4 X 12 & SMALLER	2 X 4 W/ 16d NAILS @ 12" O.C.
4 X 14 & LARGER	4 X 4
6 X 10 & SMALLER	4 X 6
6 X 12 & LARGER	6 X 6

FRAMING FOR FURTHER POST SIZE REQUIREMENTS. POSTS ARE TO CONTINUE DOWN TO FOUNDATION.

FOUNDATION NOTES

GENERAL

1. SOIL BENEATH FOOTINGS AND SLABS SHALL BE COMPACTED PER 2016 C.B.C. (90%) RELATIVE COMPACTION MINIMUM.

2. CONTINUOUS FOOTINGS AND GRADE BEAMS SHALL BE EXCAVATED TO THE DEPTH SHOWN ON THE DRAWINGS BELOW UNDISTURBED SOIL OR COMPACTED EARTH. PROVIDE 1/4" HORIZONTAL BARS ON TOP AND BOTTOM U.N.O. ON FOUND. PLAN.

3. ALLOWABLE SOIL BEARING PRESSURE IS ASSUMED TO BE 1500. PSF IF NO SOILS REPORT IS PROVIDED.

4. SLAB ON GRADE: 4 INCH NET CONCRETE SLAB WITH #3 BARS @ 18" O.C. EACH @ CENTER OF SLAB OVER 2 INCH OF SAND OVER 6 MIL. VISQUEEN OVER 2" SAND BED OVER COMPACTED SOIL U.N.O.

5. NO TRENCHES OR EXCAVATIONS FIVE FEET IN DEPTH OR GREATER INTO WHICH A PERSON SHALL BE REQUIRED TO DESCEND SHALL BE MADE WITHOUT PROPER PERMIT.

6. THE MINIMUM BOLTING FOR SILL PLATES TO FOUNDATION SHALL BE AS FOLLOWS: 5/8" DIAMETER ANCHOR BOLTS WITH 7" MIN EMBEDMENT IN CONCRETE WITH SPACING NO GREATER THAN 4 FEET O.C. NOR FURTHER THAN 12" FROM CORNERS (MIN 2 BOLTS). (SEE PRECIS) SEE THE FOUNDATION PLAN & SHEAR WALL SCHEDULE FOR FURTHER BOLTING REQUIREMENTS (FOR TWO POUR SYSTEMS, BOLTS SHALL BE EMBEDDED 4 INCH MIN. INTO FIRST POUR.)

7. PIPES OR DUCTS THAT EXCEED ONE THIRD THE SLAB OR CONC. WALL THICKNESS SHALL NOT BE PLACED IN STRUCTURAL CONC. UNLESS SPECIFICALLY DETAILED. SEE MECHANICAL AND/OR ELECTRICAL DRAWINGS FOR LOCATION OF SLEEVES, ACCESSORIES, ETC.

8. PIPES MAY PASS THRU STRUCTURAL CONC. IN SLEEVES, BUT SHALL NOT BE EMBEDDED THEREIN.

9. PROVIDE 3/4" CAMBERS AT ALL EXPOSED CORNERS.

10. SEE ARCHITECTURAL PLANS FOR MOLDS, GROOVES, ORNAMENTS, CLIPS OR GROUNDS REQUIRED TO BE CAST IN CONCRETE, AND FOR LOCATION OF FLOOR FINISHES AND SLAB DEPRESSIONS.

11. LOCATION OF POUR JOINTS SHALL BE APPROVED BY THE STRUCTURAL ENGINEER.

CONCRETE

1. UNLESS OTHERWISE NOTED ON PLANS, CONCRETE SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 2500 PSI AT 28 DAYS.

2. FINE C-90 CONCRETE AGGREGATE SHALL CONFORM TO A.S.T.M. C-33, USE 3000 P.S.I. CONC. @ GRADE BEAMS. CEMENT SHALL CONFORM TO A.S.T.M. C-150 (STANDARD BRAND, PORTLAND CEMENT) TYPE I (USE TYPE V CEMENT IF NOTED IN SOILS REPORT)

3. CONCRETE SHALL BE MACHINE-MIXED USING A MAXIMUM OF 7" GALLONS OF WATER PER SACK OF CEMENT. READY MIX CONCRETE SHALL BE MIXED AND DELIVERED IN ACCORDANCE WITH ASTM C-94 MIXED AT A RATE OF 5 SACKS OF CEMENT PER CUBIC YARD. MAXIMUM SLUMP SHALL BE 4 INCH AS MEASURED BY THE ASTM STANDARD METHOD OF TESTING FOR SLUMP OF PORTLAND CEMENT CONCRETE.

4. DRY PACK SHALL CONSIST OF 1 PART CEMENT, 4 PARTS SAND, BASED ON DRY LOOSE VOLUMES AND NOT LESS THAN 1/4 PART, NOR MORE THAN 1/2 PART, LINE PUTTY OR DRY HYDRATED LIME, DRY PACK SHALL OBTAIN A MINIMUM 14,000 LB. COMPRESSIVE STRENGTH OF 2000 PSI AT 28 DAYS.

5. ADDING CALCIUM CHLORIDE TO CONCRETE OR CEMENT IS NOT PERMITTED.

6. CONC. SHALL BE KEPT MOIST FOR 10 DAYS FOR PROPER CURING.

REQUIREMENTS FOR CONCRETE EXPOSED TO SULFATE-CONTAINING SOLUTIONS (ACI 4.3)

SULFATE EXPOSURE	CEMENT TYPE	WATER-CEMENT RATIO	COMPRESSIVE STRENGTH
NEG. IGI BLE	NOT REGULATED		2500 psi
MODERATE	I, II	0.50	4500 psi
SEVERE	V	0.45	4500 psi
VERY SEVERE	V	0.45	4500 psi

CONCRETE BLOCK MASONRY

1. CONCRETE BLOCK SHALL CONFORM TO A.S.T.M. C-90 MED. WT. GRADE N UNITS, WITH MIN. COMP. STRENGTH OF 1500 PSI. ALL CMU BLOCKS SHALL BE LAD UP IN RUNNING OR COMMON BOND CONFIGURATION.

2. MORTAR SHALL CONFORM TO ASTM C-270, TYPE S, WITH MINIMUM COMPRESSIVE STRENGTH OF 2000. PSI AT 28 DAYS.

MIX: 1 PART PORTLAND CEMENT, 12 PART LIME PUTTY, 4 PARTS SAND. } VOLUME

3. GROUT SHALL CONFORM TO ASTM C-476, WITH MINIMUM COMPRESSIVE STRENGTH OF 2000. PSI AT 28 DAYS.

MIX: 1 PART PORTLAND CEMENT, 3 PARTS SAND, 2 PARTS PEA GRAVEL. } VOLUME

WATER SUFFICIENT TO ALLOW GROUT TO FLOW INTO ALL JOINTS.

4. CELLS SHALL BE IN VERTICAL ALIGNMENT TO PROVIDE A MIN. UNOBSTRUCTED CORE OF 3" X 3". DOWELS FROM FOOTINGS SHALL BE SET TO ALIGN WITH CORE. REINFORCING BARS SHALL BE SET TO ALIGN WITH CORE.

5. ALL CELLS BELOW FINISHED GRADE AND ALL CELLS WITH REINFORCING, ANCHORS OR INSERTS SHALL BE FILLED SOLID WITH GROUT.

6. CONCRETE SURFACES SHALL BE CLEANED OF ALL LAITANCE PRIOR TO SETTING OF BLOCKS.

7. PROVIDE VERTICAL CONSTRUCTION JOINTS AT 40 FT. O.C.

8. MINIMUM LAP FOR ALL STEEL IS 6 BAR DIAMETER, OR 24 INCHES, WHICHEVER IS GREATER.

9. IF WORK IS STOPPED FOR ONE HOUR OR LONGER, PROVIDE HORIZONTAL CONSTRUCTION JOINTS BY STOPPING GROUT 1-1/2 INCH BELOW THE TOP OF THE BLOCK.

10. CLEANOUT OPENINGS MUST BE PROVIDED IN CMU WALLS WHICH ARE TO BE HIGH LIFT GROUTED. (OVER 4 FEET) AT BOTTOM COURSE.

IN SOLID GROUTED WALLS CLEANOUTS MUST BE PROVIDED AT NO MORE THAN 32 INCHES ON CENTER FOR PARTIALLY GROUTED WALLS CLEANOUTS MUST BE PROVIDED NO MORE THAN 48 INCHES O.C. WHEN CLEANOUTS ARE REQUIRED, THEY SHALL BE SEALED AFTER INSPECTION AND BEFORE GROUTING.

REINFORCING STEEL

1. REINFORCING STEEL, #3 AND #4 GRADE 40, #5 AND LARGER GRADE 60 PER A.S.T.M. A615.

2. LOW HYDROGEN WELDING RODS SHALL BE USED FOR ALL WELDING OF REINFORCING BARS.

3. BARS NOTED AS "CONT" TYPICAL WALL REINFORCING AND VERTICAL COLUMN REINFORCING SHALL HAVE A MINIMUM SPICE OF 50 BAR DIAMETERS LAP IN MASONRY OR 40 BAR DIAMETERS MINIMUM IN CONCRETE. OTHERWISE NOTED.

4. REINFORCING SHALL BE SPLICED ONLY AS SHOWN OR NOTED. OTHER SPLICES SHALL BE APPROVED BY THE STRUCTURAL ENGINEER.

5. SPLICES IN ADJACENT HORIZONTAL WALL REINFORCING BARS SHALL BE STAGGERED 4 FEET UNLESS OTHERWISE NOTED.

6. PROVIDE DOWELS IN FOOTINGS AND/OR GRADE BEAMS THE SAME SIZE AND NUMBER AS VERTICAL WALL OR COLUMN REINFORCING. DOWELS SHALL HAVE A MINIMUM PROJECTION EQUAL TO STANDARD LAP SPLICE UNLESS OTHERWISE NOTED.

7. ALL REINFORCING, ANCHOR BOLTS, AND OTHER INSERTS SHALL BE SECURED IN PLACE PRIOR TO PLACEMENT OF CONCRETE OR GROUTING OF MASONRY.

8. PROVIDE THE FOLLOWING MINIMUM PROTECTIVE COVERING OF CONCRETE:

BELOW GRADE (UNFORMED):	3" CLEAR
BELOW GRADE (FORMED):	2" CLEAR
WALLS	1" CLEAR
COLUMNS	1.5" CLEAR
BEAMS AND GIRDERS	1.5" CLEAR
STRUCTURAL SLAB (ABOVE GRADE)	3/4" CLEAR

9. #5 OR LARGER REINFORCING BARS SHALL NOT BE RE-BENT WITHOUT APPROVAL OF THE STRUCTURAL ENGINEER.

GRADING NOTES

1. A GRADING PERMIT SHALL BE OBTAINED PRIOR TO ANY GRADING.

2. ALL FILL, ONE FOOT & GREATER SHALL BE CERTIFIED AND TESTED AS TO RELATIVE COMPACTION PER U.B.C.

3. ALL FILL SHALL BE COMPACTED IN ACCORDANCE WITH ASTM D-1557, TO MAXIMUM OF 90% DENSITY.

4. ALL UTILITY TRENCH BACKFILLS SHALL BE IN ACCORDANCE WITH THE SOILS ENGINEER'S RECOMMENDATIONS.

STRUCTURAL STEEL

1. STRUCTURAL STEEL SHALL CONFORM TO ASTM A36 (Fy=36 KSI) FOR PLATES AND TO ASTM A502/Fy=50 KSI) FOR W-SHAPED STEEL SECTIONS.

2. CORTEN STEEL SHALL CONFORM TO ASTM A588, Fy=50, KSI.

3. STAINLESS STEEL SHALL CONFORM TO ASTM A276 TYPE 304-HOT ROLLED, Fy=18. KSI.

4. FABRICATION, ERECTION & PAINTING SHALL COMPLY WITH THE AISC SPECS. CHAPTER M, THIRTEENTH EDITION.

5. ALL BOLTS FOR STEEL MEMBERS SHALL CONFORM TO ASTM A325 OR A490, UNLESS OTHERWISE NOTED.

6. HIGH TENSILE BOLTS WHERE INDICATED ON THE PLANS OR DETAILS SHALL BE THE "FRICTION TYPE" TYPE AND THERE SHALL BE NO PAINT, OIL, LAQUER, OR GALVANIZING BETWEEN THE CONTACT SURFACES. HIGH TENSILE BOLTS SHALL CONFORM TO ASTM A325 OR A490.

7. HIGH STRENGTH BOLTS SHALL HAVE LOAD INDICATOR WASHERS TO SERVE AS A DIRECT TENSION INDICATOR INSTALLATION FOR HIGH STRENGTH BOLTS SHALL REQUIRE INSPECTION BY A DEPUTY INSPECTOR.

8. ANCHOR RODS SHALL BE ASTM F-1554 GRD. 55 KSI U.N.O. ALL ANCHOR RODS SHALL BE HEADED RODS ANCHOR ROD WASHER SHALL BE ASTM A308. NUTS SHALL BE ASTM A303.

9. PIPE COLUMNS SHALL CONFORM TO ASTM A-53 GRADE B.

10. STEEL TUBE SHAPED MEMBERS SHALL CONFORM TO ASTM A-501 OR A-500 GRADE B.

11. WHERE FINISH IS ATTACHED TO STRUCTURAL STEEL, PROVIDE HOLES FOR 1/2" WELDED STUDS AT 4 FEET O.C. FOR THE ATTACHMENT OF WALLERS. SEE ARCHITECTURAL DRAWINGS FOR FINISHES.

12. OPEN WEB JOISTS SHALL COMPLY WITH THE STANDARDS OR "THE STEEL JOIST" INSTITUTE.

13. STEEL STUDS, JOIST, TRACKS & BRIDGING: ASTM A-575 GRADE "E" Fy = 50 KSI 12, 14 & 16 GA. ASTM A-575 GRADE "C" Fy = 33 KSI 18 & 20 GA.

14. SPECIAL INSPECTION OF HIGH-STRENGTH A325 AND A490 BOLTS SHALL BE IN ACCORDANCE WITH APPROVED NATIONALLY RECOGNIZED STANDARDS AND REQUIREMENT OF SECTION 1701.

15. SHOP DRAWINGS SHALL BE PROVIDED TO ENGINEER OR ARCHITECT OF RECORD FOR REVIEW PRIOR TO FABRICATION.

STRUCT STEEL WELDING

1. WELDING SHALL BE DONE BY THE ELECTRIC SHIELDED ARC PROCESS W/ E70XX WELD ELECTRODES AND SHALL COMPLY WITH A.W.S. SPECIFICATIONS FOR WELDING AND FABRICATION.

2. WELDING SHALL BE PERFORMED BY CERTIFIED WELDERS WHO ARE APPROVED BY THE LOCAL AUTHORITY USING ARC PROCESS WITH E70XX ELECTRODES.

3. ALL FIELD WELDS SHALL HAVE CONTINUOUS INSPECTION PER CBC (1701) UNLESS OTHERWISE NOTED.

4. ALL BUTT WELDS SHALL BE FULL PENETRATION U.N.O.

5. A CERTIFICATE OF FABRICATION FROM THE SHOP PERMANENTLY WELDING OR A REPORT FROM THE SPECIAL INSPECTOR MUST BE FURNISHED TO THE JOB INSPECTOR PRIOR TO FRAMING APPROX. 50% COMPLETE.

6. WELDED, FULLY RESTRAINED CONNECTION BETWEEN MEMBERS OF ORDINARY MOMENT FRAMES OR SMALL MOMENT-RESISTING FRAMES SHALL HAVE SPECIAL CONTINUOUS INSPECTION AND CONNECTION TESTING BY NONDESTRUCTIVE METHODS PER SECTION 1703.

7. FIELD WELDING OF REINFORCING STEEL SHALL BE DONE BY WELDERS SPECIFICALLY CERTIFIED FOR REINFORCING STEEL WELDING. BEFORE WELDING, THE "CARBON EQUIVALENT" (CE) OF STEEL SHALL BE DETERMINED. IF THE (CE) OF STEEL IS MORE THAN 0.75%, THEY SHALL NOT BE WELDED.

GENERAL NOTES

PLYWOOD SHEATHING	CONNECTION: (TABLE 2304.9.1)
B.N.	1. JOISTS TO SILL OR GURDER, TOE NAIL _____
E.N.	2. BRIDGING TO JOISTS, TOE NAIL EA. END _____
F.N.	3. 1X6 SUBFLR. OR LESS TO EA. JST., FACE NAIL _____
	4. WIDER THAN 1X6 SUBFLR., FACE NAIL _____
	5. " SUBFLR. TO JST. OR GURDER, BUND & FACE NAIL _____
	6. SILL PLATE TO JST. OR BLK'G, FACE NAIL _____
	7. TOP PLATE TO STUD, END NAIL _____
	8. RAFT. BLK'G TO TOP PLATE, FACE OR TOE NAIL _____
	9. STUD TO SILL PLATE, TOE NAIL _____
	10. DOUBLE STUD, FACE NAIL _____
	11. DOUBLE TOP PLATES, FACE NAIL _____
	12. TOP PLATES LAPS & INTERSECTIONS, FACE NAIL _____
	13. CONTINUOUS HEADER, TWO PIECES _____
	14. CEILING JOISTS TO PLATE, TOE NAIL _____
	15. CONTINUOUS HEADER TO SILL, TOE NAIL _____
	16. CEILING JOISTS, LAPS O/ PARTITIONS, FACE NAIL _____
	17. CEILING JOISTS TO PARALLEL RAFTERS, FACE NAIL _____
	18. RAFTER TO TOP PLATE, TOE NAIL _____
	19. 1" BRACE TO EA. STUD & PLATE, FACE NAIL _____
	20. 1X8 SHTG. OR LESS TO EA. BEARING WALL, FACE NAIL _____
	21. WIDER THAN 1X8 SHTG. TO EA. BEARING WALL, FACE NAIL _____
	22. BUILT-UP CORNER STUDS _____
	23. BUILT-UP GRADERS & BEAMS _____
	24. 2" PLANKS _____
	25. PARTICLE BD. - WALL SHTG. (TO FRMG.) _____
	26. PLYWOOD SUBFLR. RF. & WALL SHTG. (TO FRMG.):
	1/2" & LESS _____
	3/8" -

1 FOUNDATION PLAN

1 1ST FLOOR FRAMING PLAN
SCALE: 1/4"=1'-0"


FOOTING SCHEDULE			
TYPE	WIDTH	DEPTH	REBAR
CF-1	2'-0"	2'-0"	2 #4 TOP & BOTTOM

PAD FOOTING SCHEDULE			
TYPE	WIDTH	DEPTH	REBAR
PF-1	2'-0"	24"	2 #4 EACH WAY
PF-2	3'-0"	24"	3 #4 EACH WAY

FOUNDATION SHOULD BE PRESSURE TREATED, OR
FOUNDATION GRADE REDWOOD

"HOLD-DOWN CONNECTORS BOLT INTO WOOD
FRAMING REQUIRE APPROVED PLATE WASHERS"

"HOLD-DOWN SHOULD BE RE-TIGHTENED JUST PRIOR TO COVERING THE WALL FRAMING.




GENERAL HOLDOWN NOTES (APPLIES TO ALL HOLDOWNS)


HOLDOWN SCHEDULE										KEYNOTES
SIMPSON TYPE	HOLDOWN PART	POST FASTENERS	HOLDOWN ANCHORS			BOLT TYPE MINIMUM EMBED	EPOXY RETROFIT MIN. DIST. FROM CORNER	MIN STEM WELD ¹⁰		
			BOLT DIAMETER	MONOLITHIC SST TYPE	TWO-POUR SST TYPE					
(2) CS16	(2) 2x STUDS	(3) 8/8 COMMON @ EA STUD	N/A	N/A	N/A	N/A	N/A	N/A	7.9	
STD 14/ STD16K	(2) 2x STUDS	(3) 8/8 10G COMMON	N/A	N/A	N/A	N/A	N/A	USE PHOS #6 MINSTEEL	6", 3, 6, 11	
HDU4	(2) 2x STUDS	(1) S95 14x12-12 WOOD SCREWS	5/8" Ø	SSTB16	SSTB16	16-5/8"	5"	5"	1.5	
HDU5	(2) 2x STUDS	(1) S95 14x12-12 WOOD SCREWS	5/8" Ø	SSTB20	SSTB24	20-5/8"	5"	5"	1.5	
HDU4	(2) 2x STUDS	(1) S95 14x12-12 WOOD SCREWS	5/8" Ø	SSTB20	SSTB24	20-5/8"	5"	5"	1.5	
HDU11	(2) 6x6 POST	(3) S95 14x12-12 WOOD SCREWS	1" Ø	SST1 x30	N/A	24"	8"	-	1.5	

KEYNOTES


1. EITHER "BOLT" OR "STB" ANCHORS MAY BE USED. "BOLT" TYPE IS DEFINED AS: THREADED ROD OR BOLT W/ DBL NUT + WASHER ASSEMBLY. "L", "BOLT" OR "J" BOLT. SEE DET. 3/3XN3 IN CONJUNCTION WITH THE SCHEDULE ABOVE FOR ANCHORAGE REQUIREMENTS. "STB" TYPE IS DEFINED AS: THE DISTANCE FROM THE TOP OF THE FOUR AND TOP OF CONCRETE (CLAS) BATHINGS SURROUNDING THE HOLDDOWN ANCHOR SHALL NOT EXCEED 4" WHERE "SHIRSON" STB OR "USP" STB TYPE ANCHORS ARE USED. SEE DET. 1/2 FOR HOLDUP/POST CONNECTION AND OTHER REQUIREMENTS.
2. "SIMPSON" N6 FASTENERS (16" "SHORTS") OR "SIMPSON" S5150 FASTENERS MAY BE USED IN LIEU OF 16G COMMONS.
3. 16G SINKERS (0.14" DIA.) MAY BE USED IN LIEU OF 10G COMMON NAILS
4. 5/8" O STB MAY BE SUBSTITUTED FOR 3/4" DIA THREADED ROD ANCHOR BOLT PROVIDED A DOUBLE WASHER IS INSTALLED BELOW NUT.
5. SEE THE MOST RECENT "SIMPSON" CATALOG DETAIL FOR WOOD SCREW FASTENER INFORMATION.
6. THE FOLLOWING HOLDDOWN SUBSTITUTIONS MAY BE USED AT CONTRACTOR DISCRETION: HTFS FOR LSTHD OR LSTHD10. HTFS FOR STB10 OR STB1010. HTFS FOR STB1010 OR STB101010.
7. FLOOR FLOOR STAIR TYPE HOLDOWN (NOT TO BE INSTALLED IN CONCRETE). PROVIDE LONGER STAIR AS NEEDED TO EXTEND TO STEEL GRADE OF FASTENER MEMBER (END GRAN NAILING NOT ALLOWED). LENGTH OF STRAP IS TO BE SUFFICIENT TO ACCOMMODATE 1/2 OF THE NUMBER OF FASTENERS PER SCHEDULE IN TO THE FASTENING MEMBERS AT EACH END OF THE STRAP (IF A FASTENING MEMBER IS NOT SCHEDULED IS THE TOTAL REQUIRED).
8. HDC ANCHOR "BOLTS" IS TO BE DIRECTLY UNDER HOLDOWN POST SEE SIMPSON CATALOG FOR MORE INFORMATION
9. A SINGLE "SIMPSON" C516 OR "USP" RS150 STRAP SHALL BE ATTACHED TO A MINIMUM OF ONE 2x OR GREATER HOLDOWN POST. PROVIDE C216 OR RS150 STRAP EACH STRAP SHALL ATTACH TO SINGLE 2x OR GREATER AND STRAPS SHALL NOT BE STACKED.
10. "MIN. STEM WIDTH" IS THE MINIMUM THICKNESS OF CONCRETE STEM WALL OR CURB WHERE THE HOLDDOWN ANCHOR IS INSTALLED. ANCHOR.
11. INDICATES STRAP TYPE FOUNDATION HOLDOWN - SEE DET. 3/3XN3, 3/4" STEM WIDTH @ STB10 & STB1014 HOLDOWNS IS ALLOWED. PROVIDE THAT A H WARDEN IS INSTALLED PER DET. 3/3XN3.




SECTION A - A
SCALE: NTS




SECTION B - B
SCALE: NTS



SECTION A-A (HOLDOWN)



SECTION C
CONCRETE STAIRWAY ON GRADE
SCALE: NTS



FOOTING PAD
SCALE: NTS



PixelArch Ltd.

- US Office:
4525 Carpinteria Ave # 636, Carpinteria CA 93014
- Canada Office
3313 Plateau Blvd. Coquitlam BC V3E 3B8
- +1 909 939 2585 info@pixearchitd.com
www.pixearchitd.com

Project Name and Address:

REMODEL AND ADU ADDITION FOR
CUONG NGUYEN
1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

DRAWING TITLE:

FOUNDATION AND FRAMING PLAN

Sheet :

Page No. :

No.


Revision/Issue

Date	
------	--


COPYRIGHT

THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD.
PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION
WITH OWNER, PIXELARCH LTD.

S.001




1 FIRST FLOOR SHEAR-WALLS PLAN
SCALE: 1/4"=1'-0"




2 LOFT FRAMING PLAN
SCALE: 1/4"=1'-0"

NOTES:
1. "MINIMUM MEMBER THICKNESS @ PANEL SEAM" REFERS TO FRAMING MEMBERS, INCLUDING PLATE AND BLOCKING, WHICH RECEIVE EDGE NAILING FROM ADJACENT PANELS.
2. 3x PLATES: USE 3x PLATES 5/8" DIAMETER ANCHOR BOLTS & 3"x3"x0.229" PLATE WASHERS AT ALL SHEAR WALL LOCATION
3. LTP4 FRAMING CLIPS: LTP4 CLIPS MAY BE USED IN PLACE OF A35 CLIPS SHOWN IN SCHEDULE WHERE LOCATION OF RIM OR BLOCKS ABOVE DOUBLE TOP PLATE ALLOWS. USE ONE LTP4 FOR EACH A35 CLIP.


SHEAR WALL SYMBOL
SHEAR WALL LENGTH → 5'-7"
SHEAR WALL TYPE → 1




4 TYP. SHEAR WALL LAYOUT
SCALE: 1"=1'-0"




7 COLUMN TO HIP BEAM CONNECTION
SCALE: 1"=1'-0"




3 TYP. WOOD STUD WALL FRAMING
SCALE: 1"=1'-0"




5 TYPICAL PLATE SPLICE DET.
SCALE: 1"=1'-0"



6 TYP. DET. @ NON BEARING WALLS
SCALE: 1"=1'-0"



8 TYPICAL STUD WALL INTERSECTION
SCALE: 1"=1'-0"



9 JOIST AND BEAM CONNECTION DETAIL
SCALE: 1"=1'-0"



PixelArch Ltd.
US Office:
4525 Carpenter Ave # 536, Carpinteria CA 93014
Canada Office:
3513 Pines Rd, Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODEL AND ADU ADDITION FOR
CUONG NGUYEN
1651 PARKSIDE AVE. SAN JOSE, CA 95125


Date: _____
Scale: _____
DRAWING TITLE:
SHEAR-WALLS & MEZZANINE PLANS

No.	Revision/Issue	Date
△		
△		
△		
△		


COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD.
PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION
WITH OWNER, PIXELARCH LTD.

Page No. :


S.002




1 ROOF FRAMING PLAN
SCALE: 1/4"=1'-0"




9 RIDGE BEAM TO POST DETAIL
SCALE: 3/4"=1'-0"




2 TYP. RIDGE CONNECTION
SCALE: 1"=1'-0"




5 CALIF. FRAM'G (PLAN VIEW)
SCALE: 1"=1'-0"




8 ROOF DIAPHRAGM NAILING
SCALE: 1"=1'-0"




3 SHEAR TRANSFER
SCALE: 1"=1'-0"



6 CALIF. FRAM'G (PLAN VIEW)
SCALE: 1"=1'-0"



4 CALIF. FRAM'G (PLAN VIEW)
SCALE: 1"=1'-0"



7 ROOF FRAMING @ RAKE WALL
SCALE: 1"=1'-0"



PixelArch Ltd.

US Office:
4525 Carpenteria Ave # 535, Carpinteria CA 93014
Canada Office:
3313 Plateau Blvd, Coquitlam BC V3E 3B8
+1 909 939 2585 info@pixelarchltd.com
www.pixelarchltd.com

Project Name and Address:

REMODEL AND ADU ADDITION FOR
CUONG NGUYEN
1651 PARKSIDE AVE. SAN JOSE, CA 95125

Date:

Scale:

DRAWING TITLE:

ROOF FRAMING PLAN

Sheet :

Page No. :

COPYRIGHT
THIS DRAWING IS AN INSTRUMENT OF SERVICE AND AS SUCH, REMAINS THE PROPERTY OF PIXELARCH LTD.
PERMISSION FOR USE OR REPRODUCTION IS LIMITED AND CAN BE EXTENDED ONLY BY WRITTEN PERMISSION
WITH OWNER, PIXELARCH LTD.

S.003


No.	Revision/Issue	Date
△		
△		
△		
△		

DESIGN CODE:

1. 2016 CBC

DESIGN LOADS:



1. Floor live load: 40 psf
2. Floor dead load: 15 psf
3. Roof dead load: 12 psf
4. Roof live load: 20 psf
5. Wind load : 10 psf roof 24psf wall
6. Ceiling dead load: 5 psf
6. Ex Wall DD = 12psf
7. In. Wall DD = 8psf
8. Concrete 145pcf



Date	5/9/2019, 6:40:53 PM	
Design Code Reference Document	ASCE7-10	
Risk Category	II	
Site Class	D - Stiff Soil	

Type	Value	Description
S_S	1.5	MCE_R ground motion. (for 0.2 second period)
S_1	0.6	MCE_R ground motion. (for 1.0s period)
S_{MS}	1.5	Site-modified spectral acceleration value
S_{M1}	0.9	Site-modified spectral acceleration value
S_{DS}	1	Numeric seismic design value at 0.2 second SA
S_{D1}	0.6	Numeric seismic design value at 1.0 second SA

Type	Value	Description
SDC	D	Seismic design category
F_a	1	Site amplification factor at 0.2 second
F_v	1.5	Site amplification factor at 1.0 second
PGA	0.5	MCE_G peak ground acceleration
F_{PGA}	1	Site amplification factor at PGA
PGA_M	0.5	Site modified peak ground acceleration
T_L	12	Long-period transition period in seconds
S_{sRT}	2.129	Probabilistic risk-targeted ground motion. (0.2 second)
S_{sUH}	1.887	Factored uniform-hazard (2% probability of exceedance in 50 years) spectral acceleration
S_{sD}	1.5	Factored deterministic acceleration value. (0.2 second)
S_{1RT}	0.747	Probabilistic risk-targeted ground motion. (1.0 second)
S_{1UH}	0.7	Factored uniform-hazard (2% probability of exceedance in 50 years) spectral acceleration.
S_{1D}	0.6	Factored deterministic acceleration value. (1.0 second)
PGA_d	0.5	Factored deterministic acceleration value. (Peak Ground Acceleration)
C_{RS}	1.128	Mapped value of the risk coefficient at short periods
C_{R1}	1.068	Mapped value of the risk coefficient at a period of 1 s



DISCLAIMER

While the information presented on this website is believed to be correct, SEAOCC / OSHPD and its sponsors and contributors assume no responsibility or liability for its accuracy. The material presented in this web application should not be used or relied upon for any specific application without competent examination and verification of its accuracy, suitability and applicability by engineers or other licensed professionals. SEAOCC / OSHPD do not intend that the use of this information replace the sound judgment of such competent professionals, having experience and knowledge in the field of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the results of the seismic data provided by this website. Users of the information from this website assume all liability arising from such use. Use of the output of this website does not imply approval by the governing building code bodies responsible for building code approval and interpretation for the building site described by latitude/longitude location in the search results of this website.


DETERMINATION OFF HOUSE FLOOR JOIST



MEMBER REPORT Level, Floor: Joist
1 piece(s) 2 x 8 Douglas Fir-Larch No. 2 @ 16" OC

PASSED

Overall Length: 10' 9"



All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal.

Design Results	Actual @ Location	Allowed	Result	LDF	Load Combination (Pattern)
Member Reaction (lbs)	415 @ 10' 6 1/2"	2109 (2.25")	Passed (20%)	-	1.0 D + 1.0 L (All Spans)
Shear (lbs)	352 @ 1' 3/4"	1305	Passed (27%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	1034 @ 5' 5 1/2"	1360	Passed (76%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.168 @ 5' 5 1/2"	0.254	Passed (L/725)	-	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.252 @ 5' 5 1/2"	0.508	Passed (L/484)	-	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	--	-	--

System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2015
Design Methodology : ASD


DETERMINATION OFF MEZZANINE FLOOR JOIST



MEMBER REPORT Level, Floor: Joist
1 piece(s) 2 x 8 Douglas Fir-Larch No. 2 @ 16" OC

PASSED

Overall Length: 11' 2 1/2"



All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal.

Design Results	Actual @ Location	Allowed	Result	LDF	Load Combination (Pattern)
Member Reaction (lbs)	295 @ 3 1/2"	1406 (1.50")	Passed (21%)	-	1.0 D + 1.0 L (All Spans)
Shear (lbs)	259 @ 10 3/4"	1305	Passed (20%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	725 @ 5' 2 1/2"	1360	Passed (53%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.110 @ 5' 2 1/2"	0.246	Passed (L/999+)	-	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.166 @ 5' 2 1/2"	0.492	Passed (L/713)	-	1.0 D + 1.0 L (All Spans)
TJ-Pro™ Rating	N/A	N/A	--	-	--

System : Floor
Member Type : Joist
Building Use : Residential
Building Code : IBC 2015
Design Methodology : ASD

DETERMINATION OFF HOUSE FLOOR BEAM



MEMBER REPORT Level, Floor: Drop Beam
1 piece(s) 4 x 10 Douglas Fir-Larch No. 2

PASSED

Overall Length: 6' 11"



All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal.

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	2103 @ 2"	5206 (3.50")	Passed (40%)	—	1.0 D + 1.0 L (All Spans)
Shear (lbs)	1457 @ 1' 3/4"	3885	Passed (38%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	3295 @ 3' 5 1/2"	4492	Passed (73%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.046 @ 3' 5 1/2"	0.219	Passed (L/999+)	—	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.070 @ 3' 5 1/2"	0.329	Passed (L/999+)	—	1.0 D + 1.0 L (All Spans)

System : Floor
Member Type : Drop Beam
Building Use : Residential
Building Code : IBC 2015
Design Methodology : ASD

DETERMINATION OFF MEZZANINE FLOOR BEAM




MEMBER REPORT

Level, Floor: Drop Beam
2 piece(s) 1 3/4" x 9 1/4" 2.0E Microllam® LVL

PASSED

Overall Length: 16' 9 1/2"



All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal.

Design Results	Actual @ Location	Allowed	Result	LDF	Load: Combination (Pattern)
Member Reaction (lbs)	5805 @ 11' 6 1/2"	18375 (7.00")	Passed (32%)	—	1.0 D + 1.0 L (All Spans)
Shear (lbs)	2813 @ 10' 5 3/4"	6151	Passed (46%)	1.00	1.0 D + 1.0 L (All Spans)
Moment (Ft-lbs)	-5892 @ 11' 6 1/2"	11204	Passed (53%)	1.00	1.0 D + 1.0 L (All Spans)
Live Load Defl. (in)	0.147 @ 5' 6 7/16"	0.369	Passed (L/908)	—	1.0 D + 1.0 L (All Spans)
Total Load Defl. (in)	0.243 @ 5' 6 1/8"	0.554	Passed (L/546)	—	1.0 D + 1.0 L (All Spans)

System : Floor
Member Type : Drop Beam
Building Use : Residential
Building Code : IBC 2015
Design Methodology : ASD

- Deflection criteria: LL (L/360) and TL (L/240).
- Top Edge Bracing (Lu): Top compression edge must be braced at 16' 10" o/c unless detailed otherwise.
- Bottom Edge Bracing (Ll): Bottom compression edge must be braced at 16' 10" o/c unless detailed otherwise.
- -557 lbs uplift at support located at 16' 5 1/2". Strapping or other restraint may be required.

DETERMINATION OF RIDGE BEAM




MEMBER REPORT

PASSED

Level, Roof: Flush Beam

3 piece(s) 1 3/4" x 18" 2.0E Microllam® LVL

Overall Length: 29' 11"



All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal.

Design Results	Actual @ Location	Allowed	Result	LDF	Load Combination (Pattern)
Member Reaction (lbs)	6351 @ 4"	13945 (4.25")	Passed (46%)	—	1.0 D + 1.0 Lr (All Spans)
Shear (lbs)	5558 @ 1' 11 1/2"	22444	Passed (25%)	1.25	1.0 D + 1.0 Lr (All Spans)
Moment (Ft-lbs)	45726 @ 14' 11 1/2"	72662	Passed (63%)	1.25	1.0 D + 1.0 Lr (All Spans)
Live Load Defl. (in)	0.672 @ 14' 11 1/2"	0.975	Passed (L/523)	—	1.0 D + 1.0 Lr (All Spans)
Total Load Defl. (in)	1.436 @ 14' 11 1/2"	1.462	Passed (L/244)	—	1.0 D + 1.0 Lr (All Spans)

System : Roof
Member Type : Flush Beam
Building Use : Residential
Building Code : IBC 2015
Design Methodology : ASD
Member Pitch : 0/12

- Deflection criteria: LL (L/360) and TL (L/240).
- Top Edge Bracing (Lu): Top compression edge must be braced at 7' 10" o/c unless detailed otherwise.
- Bottom Edge Bracing (Lu): Bottom compression edge must be braced at 29' 9" o/c unless detailed otherwise.

DETERMINATION OF DORMER BEAM




MEMBER REPORT

Level, Roof: Drop Beam

PASSED

1 piece(s) 4 x 10 Douglas Fir-Larch No. 2

Overall Length: 10'



All locations are measured from the outside face of left support (or left cantilever end). All dimensions are horizontal.

Design Results	Actual @ Location	Allowed	Result	LDF	Load Combination (Pattern)
Member Reaction (lbs)	871 @ 2'	5206 (3.50")	Passed (17%)	—	1.0 D + 1.0 Lr (All Spans)
Shear (lbs)	686 @ 1' 3/4"	4856	Passed (14%)	1.25	1.0 D + 1.0 Lr (All Spans)
Moment (Ft-lbs)	2035 @ 5'	5615	Passed (36%)	1.25	1.0 D + 1.0 Lr (All Spans)
Live Load Defl. (in)	0.035 @ 5'	0.322	Passed (L/999+)	—	1.0 D + 1.0 Lr (All Spans)
Total Load Defl. (in)	0.093 @ 5'	0.483	Passed (L/999+)	—	1.0 D + 1.0 Lr (All Spans)

System : Roof
Member Type : Drop Beam
Building Use : Residential
Building Code : IBC 2015
Design Methodology : ASD
Member Pitch : 0/12

DETERMINATION OF WOOD POST



MEMBER REPORT *Level, Free Standing Post*
1 piece(s) 3 1/2" x 7" 1.8E Parallam® PSL

PASSED

Post Height: 10'

Design Results	Actual	Allowed	Result	LDF	Load: Combination [Load Group]
Slenderness	34	50	Passed (69%)	--	--
Compression (lbs)	9474	15387	Passed (62%)	1.60	1.0 D + 0.45 W + 0.75 L + 0.75 Lr [1]
Base Bearing (lbs)	9474	793800	Passed (1%)	--	1.0 D + 0.45 W + 0.75 L + 0.75 Lr [1]
Bending/Compression	0.66	1	Passed (66%)	1.00	1.0 D + 1.0 L [1]

- Axial load eccentricity for this design is 1/6 of applicable member side dimension.
- Applicable calculations are based on NDS.

Supports	Type	Material
Base	Plate	Steel

Member Type : Free Standing Post

Building Code : IBC 2015

Design Methodology : ASD

Max Unbraced Length	Comments
Full Member Length	No bracing assumed.



Drawing is Conceptual

Vertical Load	Dead (0.90)	Floor Live (1.00)	Roof Live (non-snow: 1.25)	Wind (1.60)	Comments
1 - Point (lb)	20	80	0	0	
2 - Point (lb)	720	1383	0	0	Linked from: Floor: Drop Beam, Support 1
3 - Point (lb)	1444	3380	0	0	Linked from: Floor: Drop Beam, Support 2
4 - Point (lb)	1678	0	1949	1150/-70	Linked from: Roof: Flush Beam, Support 3

DETERMINATION OF FOOTING BELLOW COLUMN

COLUMN REACTION – 11,804

$11804/1500 = 7.86 \text{ SF} < 9 \text{ SF}$

We use footing 3x3x12"H.

DETERMINATION OF FOOTING BELLOW WALL

Lateral Analysis



Type of plywood Table 4.3A							Anchor capacity					
	6.0		4.0		3.0		HDU2 SDS2.5	HDU4 SDS2.5	HDU5 SDS2.5	HDU8 SDS2.5	HDU11 SDS2.5	HDU16 SDS2.5
15/32 8d 1-3/8	730.0		1065.0		1370.0		3075.0	4565.0	5645.0	6765.0	9535.0	10770.0
	365.0		532.5		685.0					6970.0	11175.0	14390.0
15/32 10d 1-1/2	870.0		1290.0		1680.0					7870.0		14440.0
	435.0		645.0		840.0							
19/32 10d 1-1/2	950.0		1430.0		1860.0							
	475.0		715.0		930.0							

Axe 1

Wall wind Load	24.0	PSF
Roof wind load	16.7	PSF
	b	h
Wall area	14.0	x 9.0 / 1.0 = 126.0 SQ.FT.
Roof area	0.0	x 0.0 / 2.0 = 0.0 SQ.FT.
Shear wall length	25.0	ft

Wind pressure per line foot

$$= (126.0 \times 24.0 + 0.0 \times 16.7) / 25.0 = 121.0 < 520$$

Anchor bolt
calculation

Wall height	8.0
Roof height/2	0.0

Uplift F=(126.0 x 24.0 x 8.0 + 0.0 x 16.7 x(8.0 + 0.0))/ 25.0 = 9

We use HDU2 ANCHOR

Axe 2

Wall wind Load	24.0	PSF
Roof wind load	16.7	PSF
	b	h
Wall area	14.0	x 9.0 / 1.0 = 126.0 SQ.FT.
Roof area	10.0	x 0.0 / 1.0 = 0.0 SQ.FT.
Shear wall length	14.0	ft

Wind pressure per line foot

$$= (126.0 \times 24.0 + 0.0 \times 16.7) / 14.0 = 216.0 < 520$$

Anchor bolt
calculation

Wall height	8.0
Roof height/2	0.0

Uplift F=(126.0 x 24.0 x 8.0 + 0.0 x 16.7 x(8.0 + 0.0))/ 14.0 = 17

We use HDU2 ANCHOR

Axe A

Wall wind Load	24.0	PSF	
Roof wind load	16.7	PSF	
	b	h	
Wall area			= 151.0 SQ.FT.
Roof area		/ 2.0	= 161.0 SQ.FT.
Shear wall length	15.0	ft	

Wind pressure per line foot

$$= (151.0 \times 24.0 + 161.0 \times 16.7) / 15.0 = 420.8 < 520$$

Anchor bolt
calculation

Wall height	8.0
Roof height/2	5.0

Uplift F=(151.0 x 24.0 x 8.0 + 161.0 x 16.7 x(8.0 + 5.0))/ 15.0 = 420.8

We use HDU4 ANCHOR

Axe B

Wall wind Load	24.0	PSF																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
----------------	------	-----	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Wind pressure per line foot

$$= (151.0 \times 24.0 + 161.0 \times 16.7) / 17.0 = 371.3 < 520$$

Anchor bolt
calculation

Wall height	8.0
Roof height/2	5.0

Uplift F=(151.0 x 24.0 x 8.0 + 161.0 x 16.7 x(8.0 + 5.0))/ 17.0 = 371.3

We use HDU4 ANCHOR

SEISMIC ANALYSIS

FORCE DISTRIBUTION

ROOF

ROOF WEIGHT	20	PSF
PARTITION WEIGHT	5	PSF
W TOTAL	25	PSF

2ND FLOOR

FLOOR WEIGHT	15	PSF
PARTITION WEIGHT	5	PSF
W TOTAL	25	PSF
HEIGHT:	10	FT

2013 CBC / 2012 IBC, SEC. 1613; ASCE 7-10, SEC. 12.8

$V = 0.7 \times (C_s \times W) \times \rho$	R:	6.5	I:	1	SDC:	D
$C_s = S_{D1} / (R/I)$	S1:	0.6	Sds:	1	Sd1:	0.6
Cs=			Occ.		Site	
			Cat:	II	Class:	D

Check Constraints

$$C_s \text{ min} = 0.044 \times I \times S_{DS}$$

$$C_s \text{ max} = S_{D1} / T (R / I)$$

Cs min = 0.044

For S_{D1} : $S_{D1} = 2/3 \times S_{M1}$

ASCE 7-02 Eq. 9.4.1.2.5-2

$$S_{M1} = F_v \times S_1$$

ASCE 7-02 Eq. 9.4.1.2.4-2

$$S_1^a = 0.6$$

$$S_{M1} = 1$$

$$F_v^a = 1.5$$

$$S_{D1} = 0.600$$

For T: $T = C_u \times T_a$

$$T_a = C_T \times h_n^{3/4}$$

$$C_u = 1.7^a$$

$$C_T = 0.02^a$$

$$h_n = 9$$

$$T_a = 0.104$$

$$T = 0.177$$

$$C_s \text{ max} = 0.5225$$

Cs

$$\text{FINAL} = 0.1538$$

$$V = 0.7 \times (C_s \times W) \times \rho =$$

$$0.14 \quad V = 7$$

wt ht wt*ht % F	WT	HT	WT*HT	%	F	V TOTAL
-----------------	----	----	-------	---	---	---------

ROOF		25	9	225	1	4.69	4.69

HOLD DOWN CAPACITIES SHEAR WALL CAPACITIES

HDU2	HDU4	HDU5	HDU8	HDU11	HDU14	
2307	3425	4254	5904	7152	10835	lbs

SHEAR WALL DESIGN

TYPE 1	TYPE 2	TYPE 3	TYPE 4	
	280	430		lbs/ft
		860*		

SHEAR WALL DESIGN

Shear Line Level

	LENGTH	TRIBUTARY AREA	F FLR (SQ.xV)	F ADD	F TOTAL	V/FT	WALL	T/C	DL/FLR	T NET WALL DL	HDU
Line A	FT	SQ.FT	LBS	LBS	LBS	PLF	TYPE	LBS			
1ST	15.00	380.00	1782.20		1782.20	118.81	2	1188.13	80.00	588	HDU2
WIND HDU4											
Line B											
1ST	17.00	380.00	1782.20		1782.20	104.84	2	1048.35	80.00	368	HDU2
WIND HDU4											
Line 1											
1ST	25.00	380.00	1782.20		1782.20	71.29	2	712.88	80.00	-287	HDU2
Line 2											
1ST	14.00	380.00	1782.20		1782.20	127.30	2	1273.00	80.00	713	HDU2